TP-Link 16-Port Gigabit Desktop Switch with 16-Port PoE+

Model: TL-SG116P

Manufacturer: TP-LINK

EAN: 4895252500301

Product Code: 1664767

R3,345

Width: 286 mm | IGMP snooping: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Virtual LAN features: Protocol-based VLAN | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Product colour: Black | Package depth: 434 mm | Package weight: 2 kg | Auto MDI/MDI-X: Yes | LED indicators: Yes | Broadcast storm control: Yes | Power consumption (typical): 11.72 W | Jumbo frames support: Yes | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Jumbo frames: 9000 | Power over Ethernet (PoE): Yes | Input current: 0.6 A | Loop protection: Yes | AC input voltage: 220 V | Storage relative humidity (H-H): 5 - 90% | Number of queues: 4 | Housing material: Metal | Depth: 111.7 mm | Stackable: Yes | Store-and-forward: Yes | Networking standards: IEEE 802.3u | Number of VLANs: 32 | Networking standards: IEEE 802.1Q | Operating temperature (T-T): 0 - 40 °C | DC input voltage: 9 V | Full duplex: Yes | Virtual LAN features: Tagged VLAN | Package width: 227 mm | Gigabit Ethernet (copper) ports quantity: 16 | Power consumption (max): 144.28 W | Forwarding rate: 23.81 Mpps | Cable types supported: Cat4 | Link aggregation: Yes | VLAN support: Yes | Height: 25.4 mm | Package height: 70 mm | Basic switching RJ-45 Ethernet ports quantity: 16 | Power supply included:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Yes | Copper ethernet cabling technology: 1000BASE-T | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Cable types supported: Cat6 | Warnings: Do not open the case or try to repair it yourself. | Wall mountable: Yes | Rate limiting: Yes | Copper ethernet cabling technology: 100BASE-TX | Flow control support: Yes | Switch type: Unmanaged | Cable length detection: Yes | Cable types supported: Cat5 | Cable types supported: Cat5e | Copper ethernet cabling technology: 10BASE-T | Quick start guide: Yes | Switching capacity: 32 Gbit/s | Operating relative humidity (H-H): 10 - 90% | Cable types supported: Cat3 | AC input frequency: 50 Hz | Heat dissipation: 490.55 BTU/h | Packet buffer memory: 4.1 MB | Port mirroring: Yes | MAC address table: 8000 entries | Auto-negotiation: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950