CPU COOLER S_MULTI/G89.GHS2OLDC3 LIAN LI

Model: G89.GHS2OLDC36PB.00

Manufacturer: LIAN LI

EAN: 4718466023148

Product Code: 1684257

R6,391

THREE MODELS, TWO COLORS

Available in Black and White, with three model options: UNI FAN TL FLEX, UNI FAN P28 V2, and Fanless.

UNI FAN TL FLEX

Equipped with UNI FAN TL FLEX, this version delivers a balanced combination of airflow and acoustics, making it ideal for users seeking stable cooling performance with refined noise control.

UNI FAN P28 V2

Powered by UNI FAN P28 V2, this version focuses on high airflow and static pressure, designed for high-performance systems that demand maximum cooling capability.

Fanless

The Fanless version is designed for builders who prefer to integrate their own fan setup, offering full

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

flexibility to customize airflow, noise levels, and system aesthetics.

Motorized Control. Perfect Angle

HydroShift II OLED Curved features motorized vertical and horizontal adjustments for optimal viewing angles. With L-Connect 3, the pump head can be precisely positioned to fit any build.

Magnetic Hot-Swappable Display Module

The magnetic display module uses pogo-pin connectors for secure attachment and removal.
It can be installed after the system is fully built, reducing the risk of damage during assembly or transport, while making upgrades easier and safer.

UNLEASH YOUR FULLY PERSONALIZED SETUP

Powered by L-Connect 3, the curved OLED screen delivers a more immersive and flexible user experience with dynamic content support, customizable layouts, motorized adjustment, and integrated control of display, cooling, and lighting.

2D and 3D Full-Screen Themes

Offers diverse 2D and 3D themes, turning the curved OLED display into a seamless full-screen canvas.

Dynamic & Static Content with Immersive Layered Visuals

Support for dynamic and static content enables rich, expressive layouts, giving users greater creative freedom and easier content customization. Flexible layering seamlessly combines animations, themed visuals, and information modules, allowing users to build engaging displays quickly, with dual video overlap adding depth and stronger visual impact.

Personalized Custom Theme with Modular Editing

Upload your own background and build a custom dashboard with dynamic or static theme info modules. Choose your data, adjust each module’s look, and arrange every element to match your system style.

Dual and Triple Split Layouts

Maximize your screen real estate with flexible dual and triple-split layouts that allow you to divide

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

the curved OLED display into multiple independent zones. Each section is fully customizable, giving you the freedom to select personalized backgrounds and display your choice of dynamic animations or static hardware metrics.

Integrated Ambient Lighting

Soft ambient lighting enhances the display area with a refined glow, creating a more immersive visual experience while complementing the overall system aesthetic.

UNI FAN TL FLEX, Built for Style and Performance

UNI FAN TL FLEX combines a clean design with strong airflow, high static pressure, and up to 2600 RPM performance. Control fan speed and lighting via wireless L-Connect 3, with motherboard sync for RGB.

UNI FAN TL FLEX Receiver, More Control Options

The UNI FAN TL FLEX Receiver supports both wireless control through L-Connect 3 and direct motherboard control by 5V 3-pin ARGB cable, making it easier to integrate UNI FAN TL FLEX into different build setups.

UNI FAN P28 V2, Built for Ultimate Performance

Engineered for powerful airflow and efficient cooling, the P28 V2 combines high-performance design with optimized acoustics for balanced system performance.

With RGB lighting and real-time RPM feedback, it delivers both cooling capability and visual refinement for modern PC builds.

Smart Speed Control with Gradient RPM Feedback

The UNI FAN P28 V2 delivers smart and intuitive fan control. A 5-level speed slider provides instant access to five distinct fan curves, each with its own maximum speed threshold. Every level is paired with a dedicated PWM duty cycle for refined control, allowing the UNI FAN P28 V2 to perform in 5 different ways.

UNI FAN P28 V2 Receiver, Flexible Lighting Control

The UNI FAN P28 V2 Receiver also includes an LED ON/OFF switch and supports both wireless L-

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Connect 3 control and 5V 3-pin ARGB motherboard sync, giving users more flexibility to manage lighting effects across different build setups.

Compact Radiator, Broad Compatibility

The slim 400 × 122 × 24mm radiator is engineered with a single-wave fin design to improve case compatibility across mainstream chassis. Its reduced footprint makes installation easier without compromising thermal efficiency.

Hidden Tube Routing for a Streamlined Build

HydroShift II OLED Curved Series features side-mounted tubing to reduce visual clutter. Paired with the white O11 EVO RGB, components align neatly in the top chamber, highlighting the hardware, lighting, and OLED display.

Perfect Fit for O11 Vision Compact

HydroShift II OLED Curved supports flexible side-mounted radiator installation, perfectly suited for triple-glass showcase cases like the O11 Vision Compact, delivering a clean and refined build aesthetic.

BROAD COMPATIBILITY,SEAMLESS SUPPORT

HydroShift II OLED Curved offers easy installation and broad CPU socket compatibility, featuring an upgraded AM4/AM5 bracket that ensures even pressure and improved thermal performance.

Built for Long-Term Reliability

HydroShift II OLED Curved is backed by a 6-year warranty for the AIO cooling system and a 3-year warranty for the OLED display, providing long-term reliability and peace of mind for high-performance builds.

- 6.67″ 2K 60Hz curved OLED screen with built-in 3D visual effects.
- Motorized pump head supports vertical and horizontal angle adjustment.
- Magnetic hot-swappable display module for easier installation and upgrades.
- L-Connect 3 enables screen, theme, layout, lighting, and motorized control.
- High-performance pump runs up to 2400 RPM, or 2800 RPM in Turbo Mode.
- Available in UNI FAN TL FLEX, UNI FAN P28 V2, and fanless versions.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- UNI FAN TL FLEX balances airflow, pressure, and noise.
- UNI FAN P28 V2 delivers stronger cooling with speed control and RPM lighting feedback.
- Slim radiator and side-mounted tubing improve compatibility and build cleanliness.

Summary: Lian Li HydroShift II OLED Curved 360P28. Type: All-in-one liquid cooler, Fan diameter: 12 cm, Rotational speed (min): 200 RPM, Rotational speed (max): 3000 RPM, Maximum air pressure: 7.78 mmH2O. Product colour: Black | Vendor Homepage: https://lian-li.com/product/hs2-oled-curved/ | Ventiliatoriaus skersmuo: 120 | Tipas: Universalusis skystinis aušintuvas | Palaikomi procesoriaus lizdai: AM4 lizdas/AM5 lizdas/LGA 1700/LGA 1851 | Tinkama vieta: Procesorius | Sukimosi greitis (min.): 200 | Sukimosi greitis (maks.): 3000 | Triukšmo lygis (didelis greitis): 38.1 | Didžiausias oro srautas: 110.5 | Didžiausias oro slėgis: 7.78 | Ventiliatoriaus triukšmo lygis (maks.): 38.1 | Kiekis pakuotėje: 1 | Siurblio variklio greitis (maks.): 2300 | Siurblio variklio greitis (min.): 1600 | Ventiliatoriaus greitis (maks.): 3000 | Ventiliatoriaus greitis (min.): 200 | Produkto spalva: Juoda | Medžiaga: Aliuminis | Radiatoriaus medžiaga: Aliuminio | Ventiliatorių skaičius: 3 | Apšvietimo LED: Taip | Apšvietimo spalva: Daugybė | Ekrano įstrižainė: 6.67 | Ekrano tipas: OLED | Ekrano rezoliucija: 2288 x 1048 | Radiatoriaus plotis: 400 | Radiatoriaus gylis: 122 | Radiatoriaus aukštis: 24 | Vamzdžio ilgis: 475 | Ventiliatoriaus matmenys (plotis x gylis x aukštis): 120 x 124 x 28 | Bruto svoris: 3.73 | Vienetų skaičius vienoje siuntimo dėžėje: 4 | Vieneto plotis: 19.5 | Vienetų skaičius ant paletės: 0 | Shipping Box Height: 43 | Vieneto gylis: 49 | Vieneto aukštis: 24 | Name: CPU COOLER S_MULTI/G89.GHS2OLDC36PB.00 LIAN LI | Model name: HydroShift II OLED Curved 360P28

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950