Vivitek DX330 data projector Standard throw projector 4000 ANSI lumens DMD XGA (1024x768) 3D White

Model: 1PI267

Manufacturer: VIVITEK

EAN: 813097026118

Product Code: 1684548

R8,244

Warnings: Avoid placing the projector in high humidity areas to prevent damage to the unit. | Warnings: Be careful when replacing the projector lamp as it can be very hot. | Warnings: Do not look directly into the lens of the projector during operation to avoid damage to your eyes. | Cable lock slot: Yes | Supported graphics resolutions: 1920 x 1200 (WUXGA) | Display diagonal: 1.4 cm (0.55") | Weight: 2.7 kg | Product colour: White | Native aspect ratio: 4:3 | AC input voltage: 100 - 240 V | Built-in display: Yes | Display resolution: 1920 x 1200 pixels | AC input frequency: 50/60 Hz | Uniformity: 80% | Vertical synchronization (min): 23 kHz | Projector native resolution: XGA (1024x768) | Projection technology: DMD | Zoom ratio: 1.1:1 | Light source type: Lamp | Horizontal

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

synchronization (max): 102 kHz | Projector brightness: 4000 ANSI lumens | Aperture range (F-F): 2.42 - 2.62 | Horizontal synchronization (min): 15 kHz | Service life of light source (economic mode): 10000 h | Vertical synchronization (max): 120 kHz | Projection distance: 1.2 - 12 m | Service life of light source: 5000 h | Noise level (economic mode): 27 dB | Offset: 115% | Throw ratio: 1.94 - 2.16 : 1 | Zoom type: Fixed | Lamp power: 203 W | Keystone correction, vertical: 40° | Power consumption (economy mode): 200 W | Supported video modes: 576p | Supported video modes: 720p | Supported video modes: 480i | Depth: 236 mm | HDMI version: 1.4b | Audio (L/R) in: 1 | HDMI ports quantity: 1 | Width: 313 mm | Contrast ratio (typical): 30000:1 | RMS rated power: 10 W | Analog signal format system: NTSC | Power consumption (typical): 240 W | Supported video modes: 576i | Analog signal format system: PAL | Analog signal format system: SECAM | Quantity per pack: 1 pc(s) | Noise level: 33 dB | Composite video in: 1 | Cable lock slot type: Kensington | Cables included: Power | Height: 114 mm | Batteries included: Yes | Supported video modes: 1080i | Focal length range: 22.5 - 25.79 mm | Screen size compatibility: 694.4 - 7620 mm (27.3 - 300") | Supported video modes: 480p | Supported video modes: 1080p | Cables included: VGA | Product type: Standard throw projector | Power consumption (standby): 0.5 W | Remote control included: Yes | Power source: AC | 3D: Yes | Zoom capability: Yes | Manual: Yes | Built-in speaker(s): Yes | Serial interface type: RS-232 | VGA (D-Sub) ports quantity: 1 | Audio (L/R) out: 1

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950