Thermaltake Toughpower GX3 SE 750W power supply unit 24-pin ATX ATX Black

Model: PS-TPD-0750NNSAGE-3

Manufacturer: THERMALTAKE

EAN: 4711658549136

Product Code: 1684599

R2,204

Motherboard power connector: 24-pin ATX | Combined power (-12V): 3.6 W | Number of SATA power connectors: 3 | PCI Express power connectors (6+2 pin): 4 | SATA power cable length: 450 | Combined power (+5V): 110 W | Peripheral (Molex) power cable length: 150 mm | ATX version: 3.1 | Max output current (+3.3V): 18 A | PCI Express connector: Yes | Power Good signal delay range: 100 - 150 ms | Max output current (+5Vsb): 3 A | Combined power (+12V): 750 W | SATA power cable length: 150 mm | EPS power connector (4+4 pin): Yes | Motherboard power cable length: 50 cm | Bearing technology: FDB | Peripheral (Molex) power cable length: 450 | Power supply unit (PSU) form factor: ATX | Hold time: 17 ms | Combined power (+3.3V): 110 W | Max output current (+12V): 62.5 A | Power Factor Correction (PFC) type: Active | PCI Express power connectors (12+4 pin) cable length: 600 mm | Combined power (+5Vsb): 15 W | Max output current (+5V): 18 A | Compliance certificates: CE | Compliance certificates: RCM | Compliance certificates: BIS | Compliance

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

certificates: Low Voltage Directive (LVD) | Max output current (-12V): 0.3 A | Compliance certificates: CB | PCI Express power connectors (12+4 pin): 1 | Compliance certificates: UKCA | AC input frequency: 50/60 Hz | On/off switch: Yes | Width: 150 mm | Input current: 6 A | 80 PLUS certification: 80 PLUS Gold | Storage temperature (T-T): -40 - 55 °C | AC input voltage: 200 - 240 V | Purpose: PC | Total power: 750 W | Package type: Box | Storage relative humidity (H-H): 10 - 95% | Cooling type: Active | Power protection features: Overheating | Cabling type: Non-Modular | Number of fans: 1 fan(s) | Power protection features: Under voltage | Power protection features: Over current | Product colour: Black | Operating relative humidity (H-H): 20 - 85% | Power protection features: Over power | Power protection features: Short circuit | Power protection features: Over voltage | Fan diameter: 12 cm | Height: 86 mm | Operating temperature (T-T): 5 - 40 °C | Mean time between failures (MTBF): 100000 h | Efficiency: 90% | Peripheral (Molex) power connectors (4-pin): 1 | Depth: 140 mm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950