Thermaltake Toughpower GX3 SE 850W power supply unit 24-pin ATX ATX Black

Model: PS-TPD-0850NNSAGE-3

Manufacturer: THERMALTAKE

EAN: 4711658549181

Product Code: 1684600

R2,374

Compliance certificates: CB | Compliance certificates: RCM | Compliance certificates: BIS | Compliance certificates: CE | Compliance certificates: UKCA | PCI Express power connectors (12+4 pin) cable length: 600 mm | PCI Express power connectors (12+4 pin): 1 | Compliance certificates: Low Voltage Directive (LVD) | Power protection features: Over power | Operating relative humidity (H-H): 20 - 85% | Number of fans: 1 fan(s) | On/off switch: Yes | AC input voltage: 200 - 240 V | Input current: 6 A | Peripheral (Molex) power connectors (4-pin): 1 | Power protection features: Overheating | 80 PLUS certification: 80 PLUS Gold | Cooling type: Active | Depth: 140 mm | Operating temperature (T-T): 5 - 40 °C | Storage relative humidity (H-H): 10 - 95% | Width: 150 mm | AC input frequency: 50/60 Hz | Height: 86 mm | Power protection features: Under voltage | Power protection features: Over current | Power protection features: Short circuit | Power protection features: Over voltage | Product colour: Black | Storage temperature (T-T): -40 - 55 °C | Package type: Box |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Purpose: PC | Combined power (+12V): 850 W | Peripheral (Molex) power cable length: 450 | Power Factor Correction (PFC) type: Active | Max output current (+12V): 70.8 A | Efficiency: 90% | Number of SATA power connectors: 3 | Combined power (+5V): 110 W | Peripheral (Molex) power cable length: 150 mm | Motherboard power cable length: 50 cm | SATA power cable length: 150 mm | Max output current (+3.3V): 18 A | PCI Express connector: Yes | Max output current (-12V): 0.3 A | SATA power cable length: 450 | Max output current (+5V): 18 A | Combined power (+5Vsb): 15 W | Mean time between failures (MTBF): 100000 h | Max output current (+5Vsb): 3 A | Combined power (+3.3V): 110 W | PCI Express power connectors (6+2 pin): 4 | Bearing technology: FDB | Power supply unit (PSU) form factor: ATX | Hold time: 17 ms | ATX version: 3.1 | Fan diameter: 12 cm | Motherboard power connector: 24-pin ATX | Total power: 850 W | EPS power connector (4+4 pin): Yes | Cabling type: Non-Modular | Power Good signal delay range: 100 - 150 ms | Combined power (-12V): 3.6 W

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950