Thermaltake Toughpower GX3 SE 1000W power supply unit 24-pin ATX ATX Black

Model: PS-TPD-1000NNSAGE-3

Manufacturer: THERMALTAKE

EAN: 4711658549235

Product Code: 1684601

R3,060

Purpose: PC | Height: 86 mm | Operating temperature (T-T): 5 - 40 °C | Total power: 1000 W | Number of fans: 1 fan(s) | AC input voltage: 200 - 240 V | Fan diameter: 14 cm | 80 PLUS certification: 80 PLUS Gold | Power protection features: Short circuit | Power protection features: Over voltage | Power protection features: Over power | Cooling type: Active | Power protection features: Under voltage | Power protection features: Over current | Package type: Box | Power protection features: Overheating | Storage temperature (T-T): -40 - 55 °C | Peripheral (Molex) power connectors (4-pin): 4 | Product colour: Black | On/off switch: Yes | Input current: 10 A | AC input frequency: 50/60 Hz | Width: 150 mm | Storage relative humidity (H-H): 10 - 95% | Operating relative humidity (H-H): 20 - 85% | Depth: 160 mm | Efficiency: 90% | Number of SATA power cables: 2 | Compliance certificates: CB | Compliance certificates: Low Voltage Directive (LVD) | Compliance certificates: RCM | Compliance certificates: BIS | ATX version: 3.1 | Cabling type: Non-Modular | PCI

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Express power connectors (6+2 pin): 4 | Combined power (+3.3V): 100 W | Mean time between failures (MTBF): 100000 h | Power supply unit (PSU) form factor: ATX | PCI Express power connectors (12+4 pin) cable length: 600 mm | Compliance certificates: UKCA | Compliance certificates: CE | Bearing technology: FDB | PCI Express power connectors (12+4 pin): 1 | SATA power cable length: 150 mm | PCI Express connector: Yes | Combined power (+5V): 100 W | Max output current (+3.3V): 20 A | Combined power (+5Vsb): 15 W | Number of SATA power connectors: 8 | SATA power cable length: 450 | Max output current (+5Vsb): 3 A | Max output current (-12V): 0.3 A | Hold time: 17 ms | Combined power (+12V): 1000 W | EPS power connector (4+4 pin): Yes | Motherboard power connector: 24-pin ATX | Combined power (-12V): 3.6 W | Power Good signal delay range: 100 - 150 ms | Max output current (+12V): 83.33 A | Power Factor Correction (PFC) type: Active | Max output current (+5V): 20 A | Peripheral (Molex) power cable length: 150 mm | Peripheral (Molex) power cable length: 450 | Motherboard power cable length: 50 cm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950