

Thermaltake Toughpower Gt power supply unit 750 W 24-pin ATX ATX Black

Model: PS-TPT-0750FNFAGE-3

Manufacturer: THERMALTAKE

EAN: 4711475647343

Product Code: 1684602

R2,374

Certification: CE/UKCA/ICES/TUV/LVD/RCM/CB/FCC/cTUVus/BSMI/CCC/BIS/S-MARK | Max output current (+5V): 20 A | Combined power (+5Vsb): 15 W | Max output current (-12V): 0.3 A | Max output current (+5Vsb): 3 A | Power Good signal delay range: 100 - 250 ms | CPU power cable length: 70 cm | Number of SATA power connectors: 6 | Max output current (+3.3V): 20 A | Motherboard power connector: 24-pin ATX | Max output current (+12V): 62.5 A | CPU power connector (4+4 pin): Yes | Motherboard power cable length: 55 cm | SATA power cable length: 150 mm | SATA power cable length: 450 | Hold time: 17 ms | Peripheral (Molex) power cable length: 150 mm | Peripheral (Molex) power cable length: 400 mm | PCI Express power connectors (12+4 pin): 1 | PCI Express power connectors (12+4 pin) cable length: 600 mm | Width: 150 mm | Purpose: PC/Server | 80 PLUS certification: 80 PLUS Gold | Mean time between failures (MTBF): 100000 h | Input current: 10 A | Cabling type: Fully-Modular | Total power: 750 W | PCI Express power connectors (6+2 pin): 4 | AC

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

input voltage: 100 - 240 V | Peripheral (Molex) power connectors (4-pin): 4 | Depth: 140 mm | Combined power (-12V): 3.6 W | Operating temperature (T-T): 0 - 40 °C | Combined power (+12V): 750 W | Height: 86 mm | Power Factor Correction (PFC) type: Active | Storage relative humidity (H-H): 5 - 95% | Package type: Box | Combined power (+5V): 100 W | Combined power (+3.3V): 100 W | Cooling type: Active | Bearing technology: Hydraulic | On/off switch: Yes | Power protection features: Overheating | AC input frequency: 50/60 Hz | Number of fans: 1 fan(s) | ATX version: 3.1 | Power protection features: Short circuit | Power protection features: Over voltage | Power protection features: Under voltage | Power protection features: Over current | Power protection features: Over power | Fan diameter: 12 cm | Operating relative humidity (H-H): 5 - 85% | Product colour: Black | Storage temperature (T-T): -40 - 70 °C | Power supply unit (PSU) form factor: ATX

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950