

Thermaltake Toughpower GT 1000W power supply unit 24-pin ATX ATX Black

Model: PS-TPT-1000FNFAGE-3

Manufacturer: THERMALTAKE

EAN: 4711658543981

Product Code: 1684603

R3,365

AC input frequency: 50/60 Hz | Operating relative humidity (H-H): 5 - 85% | AC input voltage: 100 - 240 V | Storage temperature (T-T): -40 - 70 °C | Product colour: Black | Input current: 15 - 10 A | Operating temperature (T-T): 0 - 40 °C | Cooling type: Active | Combined power (+5V): 100 W | Mean time between failures (MTBF): 100000 h | Combined power (-12V): 3.6 W | Combined power (+5Vsb): 15 W | Width: 150 mm | Combined power (+3.3V): 100 W | SATA power cable length: 450 | Height: 86 mm | Power Factor Correction (PFC) type: Active | Power supply unit (PSU) form factor: ATX | Power protection features: Short circuit | Power protection features: Over power | Peripheral (Molex) power cable length: 150 mm | Max output current (+5Vsb): 3 A | Bearing technology: Hydraulic | 80 PLUS certification: 80 PLUS Gold | Total power: 1000 W | Peripheral (Molex) power cable length: 400 mm | Combined power (+12V): 999.6 W | Purpose: PC | SATA power cable length: 150 mm | Compliance certificates: RCM | Compliance certificates: BIS | Max output current (+12V): 83.3 A |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Compliance certificates: CB | Compliance certificates: EAC | Max output current (-12V): 0.3 A | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: ICES | On/off switch: Yes | Power protection features: Over voltage | Depth: 140 mm | Motherboard power connector: 24-pin ATX | Compliance certificates: cTUVus | Peripheral (Molex) power connectors (4-pin): 4 | ATX version: 3.1 | PCI Express power connectors (6+2 pin): 5 | Number of SATA power connectors: 6 | PCI Express power connectors (12+4 pin): 1 | Compliance certificates: BSMI | EPS power connector (4+4 pin): Yes | Compliance certificates: CCC | Fan diameter: 12 cm | Compliance certificates: CE | Cabling type: Fully-Modular | Hold time: 17 ms | Max output current (+3.3V): 20 A | Number of fans: 1 fan(s) | Max output current (+5V): 20 A | Compliance certificates: UKCA | Compliance certificates: Low Voltage Directive (LVD) | Motherboard power cable length: 55 cm | Power protection features: Under voltage | Power protection features: Over current | PCI Express power connectors (12+4 pin) cable length: 600 mm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950