



Thermaltake Toughpower GT 1200W power supply unit 24- pin ATX ATX Black

Model: PS-TPT-1200FNFACE-3

Manufacturer: THERMALTAKE

EAN: 4711658544087

Product Code: 1684604

R3,725

Compliance certificates: Low Voltage Directive (LVD) | Compliance certificates: CE | Compliance certificates: RCM | Compliance certificates: BIS | Compliance certificates: CB | Compliance certificates: EAC | Compliance certificates: CCC | PCI Express power connectors (12+4 pin): 2 | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: ICES | Compliance certificates: BSMI | Compliance certificates: UKCA | Compliance certificates: cTUVus | PCI Express power connectors (12+4 pin) cable length: 600 mm | AC input frequency: 50/60 Hz | Operating relative humidity (H-H): 5 - 85% | Operating temperature (T-T): 0 - 40 °C | Combined power (-12V): 3.6 W | Combined power (+12V): 1200 W | Combined power (+5V): 100 W | Max output current (+3.3V): 20 A | Width: 150 mm | 80 PLUS certification: 80 PLUS Gold | Power supply unit (PSU) form factor: ATX | Product colour: Black | Hold time: 17 ms | Cooling type: Active |

Combined power (+3.3V): 100 W | Max output current (+12V): 100 A | Height: 86 mm | Power Factor

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Correction (PFC) type: Active | SATA power cable length: 150 mm | Purpose: PC | SATA power cable length: 450 | Peripheral (Molex) power cable length: 400 mm | Motherboard power cable length: 55 cm | Peripheral (Molex) power cable length: 150 mm | Max output current (+5Vsb): 3 A | PCI Express power connectors (6+2 pin): 5 | Number of SATA power connectors: 6 | Peripheral (Molex) power connectors (4-pin): 4 | Storage temperature (T-T): -40 - 70 °C | Depth: 140 mm | Input current: 15 - 10 A | Mean time between failures (MTBF): 100000 h | AC input voltage: 100 - 240 V | Max output current (+5V): 20 A | Power protection features: Over power | Power protection features: Under voltage | Power protection features: Over current | EPS power connector (4+4 pin): Yes | Bearing technology: Hydraulic | Combined power (+5Vsb): 15 W | Max output current (-12V): 0.3 A | Power protection features: Short circuit | Power protection features: Over voltage | Total power: 1200 W | Cabling type: Fully-Modular | On/off switch: Yes | Number of fans: 1 fan(s) | Fan diameter: 12 cm | ATX version: 3.1 | Motherboard power connector: 24-pin ATX

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950