NET GATEWAY CLOUD INDUSTRIAL/UCG-INDUSTRIAL UBIQUITI

Model: UCG-INDUSTRIAL

Manufacturer: UBIQUITI

EAN: 810177162827

Product Code: 1689705

R13,921

Мережевий шлюз Ubiquiti Cloud Gateway Industrial 270W (UCG-Industrial)

Ruggedized, fanless 10 GbE UniFi Cloud Gateway delivering 350W of total system power for high-density PoE deployments, with advanced routing capabilities and microSD storage for full UniFi application support./

Мережевий шлюз Ubiquiti Cloud Gateway Industrial 270W (UCG-Industrial)

Ruggedized, fanless 10 GbE UniFi Cloud Gateway delivering 350W of total system power for high-density PoE deployments, with advanced routing capabilities and microSD storage for full UniFi application support.
Long Description: Ubiquiti UCG-Industrial. Product colour: Black, Mounting type: Rack/Desktop/Wall,

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

LED indicators: Status. Antenna type: Internal, Antenna connector type: RP-SMA, Antenna gain level (max): 5 dBi. Processor manufacturer: ARM, Processor family: ARM Cortex, Processor frequency: 2200 MHz. Ethernet LAN data rates: 1000,2500,10000 Mbit/s, Networking standards: IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11be, WLAN data transfer rates supported: 6,9,12,18,24,36,48,54,5.5,1,2,11,6.5,2402,1732 Mbit/s. WAN connection: Ethernet (RJ-45), SFP+ | Vendor Homepage: https://eu.store.ui.com/eu/en/products/ucg-industrial?c=DE | Summary: Ubiquiti UCG-Industrial. Product colour: Black, Mounting type: Rack/Desktop/Wall, LED indicators: Status. Antenna type: Internal, Antenna connector type: RP-SMA, Antenna gain level (max): 5 dBi. Processor manufacturer: ARM, Processor family: ARM Cortex, Processor frequency: 2200 MHz. Ethernet LAN data rates: 1000,2500,10000 Mbit/s, Networking standards: IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11be, WLAN data transfer rates supported: 6,9,12,18,24,36,48,54,5.5,1,2,11,6.5,2402,1732 Mbit/s. WAN connection: Ethernet (RJ-45), SFP+ | Montavimo tipas: Stelažinis / stalinis / sieninis | Produkto spalva: Juoda | LED indikatoriai: Būsena | Antenos tipas: Vidinis | Antenos jungties tipas: RP-SMA | Antenos stiprinimo lygis (max): 5 | Antenų kiekis: 2 | Valdiklio vaizdavimo įrenginys: Ne | Integruotas procesorius: Taip | Procesoriaus gamintojas: ARM | Procesoriaus šeima: ARM Cortex | Procesoriaus dažnis: 2200 | Įdiegtų procesorių skaičius: 1 | Vidinė atmintis: 3000 | Vidinės atminties tipas: DDR4 | Eterneto LAN duomenų perdavimo norma: 1000/10000/2500 | Tinklo standartai: IEEE 802.11a/IEEE 802.11ac/IEEE 802.11ax/IEEE 802.11b/IEEE 802.11be/IEEE 802.11g/IEEE 802.11n | „Wi-Fi“: Taip | WLAN duomenų perdavimo grečio palaikymas: 1/11/12/1732/18/2/24/2402/36/48/5.5/54/6/6.5/9 | Apkrovos balansavimas: Taip | Duomenų perdavimo sparta: 4.3 | Firewall apsauga: Taip | Tinklo adresų transliavimas (NAT): Taip | VLAN palaikymas: Taip | SIM kortelės anga: Taip | SIM daugia-kortelių skaičius: 2 | DC įėjimo lizdas: Taip | Ethernet LAN (RJ-45) portų kiekis: 5 | SFP+ prievadų skaičius: 1 | WAN portas: Ethernet (RJ-45),SFP+ | Atstatymo mygtukas: Taip | Multicast palaikymas: Taip | Paslaugos kokybės (QoS) palaikymas: Taip | Galios suvartojimas (maks.): 28 | Įėjimo įtampa: 100 - 240 | DC įėjimo įtampa: 50 - 57 | Maitinimas: 350 | Maitinimas per Eternetą (PoE): Taip | Šilumos sklaida: 85 | Apsauga nuo elektrostatinio išlydžio: Taip | Apsauga nuo elektrostatinės iškrovos (ESD; oras): 8 | Apsauga nuo elektrostatinės iškrovos (ESD; kontaktas): 4 | Elektromagnetinė (EMP) apsauga: Taip | Elektromagnetinė (EMP) apsauga (oras): 8 | Elektromagnetinė (EMP) apsauga (kontaktas): 4 | Suderinamos operacinės sistemos: Android, iOS | Aukštis: 43.7 | Ilgis: 203.5 | Plotis: 307.9 | Svoris: 2400 | Instrukcija: Taip | Kintamosios srovės adapteris: Taip | Darbo temperatūros diapazonas (TT): -30 - 50 | Darbo santykinės drėgmės diapazonas: 5 - 95 | Atitikties sertifikatai: „National Defense Authorization Act“ (NDAA)/CE/Federalinė

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

ryšių komisija (FCC)/Industry Canada (IC) | Bruto svoris: 3.5 | Neto svoris: 2.4 | Vienetų skaičius vienoje siuntimo dėžėje: 2 | Vieneto plotis: 27 | Vienetų skaičius ant paletės: 0 | Shipping Box Height: 37 | Vieneto gylis: 37 | Vieneto aukštis: 14.5 | : | : | Name: NET GATEWAY CLOUD INDUSTRIAL/UCG-INDUSTRIAL UBIQUITI

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950