CASE FAN 120MM TL FLEX REVERSE/WHITE G9F.12RTL1F1W.00 LIAN LI

Model: G9F.12RTL1F1W.00

Manufacturer: LIAN LI

EAN: 4718466023483

Product Code: 1691824

R1,192

MULTIPLE OPTIONS, COMPLETE FLEXIBILITY

Available in LCD and LED versions, with black, white, standard, and reverse-blade options to suit any build configuration.

Infinite Glow, Unified Design

UNI FAN TL FLEX and TL LCD FLEX feature refined lighting with a seamless infinity mirror design. The ARGB light strip extends around the mounting screws for a cleaner, more unified look.

Engineered Without Compromise

Designed for enthusiasts who demand maximum cooling, TL FLEX pairs premium LCP fan blades with an ultra-tight 0.6 mm blade clearance and precision FDB bearings to deliver exceptional airflow,

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

static pressure, and stability—all certified by PPLP Lab A-Class Performance.

Enhanced Bearing Design

A newly engineered oil retention groove (shown in red) around the fan bearing helps keep lubricant precisely where it’s needed, ensuring consistent lubrication for reduced friction, quieter operation, and long-term bearing reliability.

FLEXIBLE CONTROL, YOUR WAY

Using the included FLEX receivers, the UNI FAN FLEX Series supports both L-Connect 3 and motherboard control, giving you the flexibility to choose the control mode that best fits your setup.

CONTROL MORE, CABLE LESS

Connect both the 4-Pin PWM and 5V 3-Pin ARGB cables to your motherboard, then pair with the L-Wireless Controller for flexible fan speed and lighting control. Built-in LCD themes and motherboard ARGB synchronization create a cleaner build with seamless personalization.

Connect the 5V 3-Pin ARGB cable to unify fan lighting with your motherboard RGB ecosystem, bringing a cohesive visual style while preserving flexible fan speed control.

Built for Motherboard Sync

Control fan speed and lighting through the motherboard BIOS or motherboard software without a wireless controller. For LCD fans, first connect via USB to L-Connect 3 to set the default offline theme. Once saved, the content remains active, allowing users to switch to the 5V 3-Pin ARGB cable for independent lighting control without keeping the software connected in real time.

One Controller, Complete Control

Driven by 2.4GHz wireless technology, one L-Wireless Controller unifies up to 10 groups of compatible LIAN LI devices through a compact rear I/O USB receiver and dedicated PWM receivers, creating a cleaner, more streamlined wireless ecosystem.

Exclusive Software, Complete Customization

With L-Connect 3, lighting effects and fan curves are fully within your control. Built-in presets and customizable profiles let you fine-tune every detail and create a system that reflects your style.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Custom Device Naming

Customize fan names and drag to rearrange their order, making it easy to build smooth, personalized lighting flows that match your setup.

Visual Identification, Easy Pairing

Pair fans in seconds through L-Connect 3. Quickly locate each fan with Device Finder, or bind all detected devices at once for a faster, smoother setup.

- Infinity-mirror ARGB lighting with a cleaner, unified visual design
- Supports L-Connect 3, motherboard ARGB sync, and PWM fan control
- Multiple control modes for wireless themes, USB LCD customization, or motherboard control
- Daisy-chain design and FLEX receivers simplify cable routing and expansion
- FDB bearing and 0.6 mm blade clearance deliver strong, stable cooling performance

Summary: Lian Li Uni Fan TL Flex 120. Type: Fan, Fan diameter: 12 cm, Rotational speed (min): 200 RPM, Rotational speed (max): 2300 RPM, Maximum air pressure: 2.66 mmH2O, Bearing type: Fluid Dynamic Bearing (FDB). Voltage: 6 - 13.2 V. Product colour: White | Vendor Homepage: https://lian-li.com/product/uni-fan-tl-flex/ | Ventiliatoriaus skersmuo: 120 | Tipas: Ventiliatorius | Tinkama vieta: Kompiuterio korpusui | Sukimosi greitis (min.): 200 | Sukimosi greitis (maks.): 2300 | Triukšmo lygis (didelis greitis): 34 | Didžiausias oro srautas: 83.4 | Didžiausias oro slėgis: 2.66 | Dvipusiai ašmenys: Taip | Impulsų pločio moduliacijos (PWM) palaikymas: Taip | Ventiliatoriaus laikiklio tipas: Hidrodinaminis guolis (FDB) | Kiekis pakuotėje: 1 | Produkto spalva: Balta | Medžiaga: Poliamidas/Skystųjų kristalų polimerai (LCP) | Apšvietimo LED: Taip | LED diodų skaičius: 26 | Apšvietimo spalva: Daugybė | Šviesos diodų jungties tipas: 3 jungčių | Ventiliatoriaus jungtis: Keturių kontaktų | Įtampa: 6 - 13.2 | Ventiliatoriaus energijos suvartojimas: 3.72 | LED įtampa: 5 | Ventiliatoriaus srovė: 0.31 | Ventiliatoriaus matmenys (plotis x gylis x aukštis): 120 x 124 x 28 | Pakuotės tipas: „Box“ | Pridėti kabeliai: 3 jungčių | Pridedamas RGB valdiklis: Taip | Bruto svoris: 0.36 | Neto svoris: 0.3 | Vienetų skaičius vienoje siuntimo dėžėje: 30 | Vieneto plotis: 13.5 | Vienetų skaičius ant paletės: 0 | Shipping Box Height: 22 | Vieneto gylis: 3.5 | Vieneto aukštis: 18 | Name: CASE FAN 120MM TL FLEX REVERSE/WHITE G9F.12RTL1F1W.00 LIAN LI | Model name: Uni Fan TL Flex 120

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950