Switch DAHUA S3006-4GT-36 Switch type Unmanaged Form factor Desktop/Wall-Mounting 4xRJ-45 ports RJ-45 Ports Type Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Yes 4xPower over Ethernet (PoE) ports quantity Total Power over Ethernet (PoE) budget 36 W

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

S3006-4GT-36

Model: S3006-4GT-36

Manufacturer: DAHUA

EAN: 6939554940224

Product Code: 1694121

R1,067

Highly reliable, the unmanaged PoE switch is equipped with a high performance switching engine, has large buffer memory and optimizes transmission performance. The device supports long distance PoE, and the PoE port provides up to 30 W, making it suitable for small and medium sized settings that require PoE power supplies. It can operate in temperatures ranging -10°C to 55°C. It also features EMC and has protection against overvoltage, overcurrent, static electricity, lightning strikes, pulses and other types of interference.

Plug and Play

Hassle-free, it does not require any configuration. Simply use after it is powered on.

Easy Installation

Both desktop and wall mount installation are supported, making it suitable for a wide variety of scenarios.

Long Distance PoE

The transmission distance of a PoE port can be up to 250 m, meeting the requirement of wired transmission (bandwidth reduced to 10 Mbps).

Wide Operating Temperature

Supports working at ambient temperatures of –10 °C to +55 °C, and has built-in professional

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

lightning-proof circuits that effectively reduce the impact of thunderstorms on network systems and improve system robustness, allowing the device to adapt to harsh environments.

- Easy to install, and is plug and play
- Meets the requirements of IEEE802.3af and IEEE802.3at standards
- Performs long-distance transmission
- With its solid full metal design, the device has great heat dissipation and no fan
- Wide operating temperature ranging from –10 °C to +55 °C
- Supports wall mount and desktop mount

Summary: Dahua Technology PoE S3006-4GT-36. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 4. MAC address table: 2000 entries, Switching capacity: 12 Gbit/s. Networking standards: IEEE 802.3af, IEEE 802.3at, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x. DC input voltage: 53 V. Power connector: DC-in jack. Power over Ethernet (PoE). Wall mountable, Form factor: Desktop/Wall-Mounting | Vendor Homepage: https://transmission.dahuasecurity.com/en/product-list/Business/Switches/PoESwitchForSecurity/S3006-4GT-36 | Perjungimo tipas: Ne-valdomas | Pagrindinių perjungimo RJ-45 eterneto prievadų skaičius: 4 | Pagrindinių perjungimo RJ-45 eterneto prievadų tipas: Gigabit Ethernet (10/100/1000) | Aukštynkryčio ryšio prievadų skaičius: 2 | Maitinimo jungtis: DC lizdas | Tinklo standartai: IEEE 802.3/IEEE 802.3ab/IEEE 802.3af/IEEE 802.3at/IEEE 802.3u/IEEE 802.3x | 10G parama: Ne | Eterneto LAN duomenų perdavimo norma: 10,100,1000 | Perjungimo pajėgumas: 12 | Persiuntimo dažnis: 8.928 | Adreso lentelės dydis: 2000 | Jumbo Frames palaikymas: Taip | „Jumbo“ kadrai: 9216 | Paketo buferio atmintis: 1 | Stovo montavimas: Ne | Forma: Stalinis / tvirtinamas prie sienos | Produkto spalva: Mėlyna | Korpuso medžiaga: Metalas | LED indikatoriai: Taip | Montuojamas ant sienos: Taip | Maitinimo šaltinis: DC/PoE | Pridėtas maitinimo šaltinis: Taip | DC įėjimo įtampa: 53 | Įvesties srovė: 0.8 | Galios suvartojimas (maks.): 40.7 | Maitinimas per Eternetą (PoE): Taip | Palaikomas maitinimo per eternetą (en. PoE) tipas: Active PoE | Maitinimo per Eternetą (PoE) prievadų skaičius: 4 | Bendrosios galios per Eternetą (PoE) charakteriskos: 36 | Darbo temperatūros diapazonas (TT): -10 - 55 | Sandėliavimo temperatūros norma (T-T): -40 - 75 | Darbo santykinės drėgmės diapazonas: 10 - 90 | Sandėliavimo santykinis drėgmės diapazonas: 5 - 95 | Plotis: 84.3 | Ilgis: 115.5 | Aukštis: 27 | Svoris: 200 | Pridėti kabeliai: Energija | Instrukcija: Taip | Pakuotės tipas: „Box“ | Pakuotės plotis: 115 | Pakuotės gylis: 196 | Pakuotės aukštis: 85 | Paketo svoris: 650 | Atitikties sertifikatai: CE | Bruto svoris: 0.7 | Neto svoris: 0.2 | Vienetų skaičius vienoje siuntimo dėžėje: 1 | Vieneto plotis: 11.5 | Vienetų skaičius ant paletės:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

0 | Shipping Box Height: 8.5 | Vieneto gylis: 20 | Vieneto aukštis: 8.5 | Name: NET SWITCH 6PORT 4POE/S3006-4GT-36 DAHUA | Model name: S3006-4GT-36

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950