Ubiquiti G5 Flex Dome IP security camera Indoor & outdoor 2688 x 1512 pixels Ceiling/Wall/Desk

Model: UVC-G5-FLEX

Manufacturer: UBIQUITI

EAN: 810084690222

Product Code: 1694199

R3,895

Certification: FCC, IC, CE | Bluetooth: No | Type: IP security camera | Maximum resolution: 2688 x 1512 pixels | Form factor: Dome | Reset button: Yes | Operating relative humidity (H-H): 0 - 90% | Operating temperature (T-T): -20 - 40 °C | Weight: 170 g | LED indicators: Yes | Built-in microphone: Yes | Power source type: PoE | Mounting kit: Yes | Connectivity technology: Wired | Ethernet LAN (RJ-45) ports: 1 | Supported graphics resolutions: 2688 x 1512 | Processor model: ARM Cortex-A7 | Product colour: White | International Protection (IP) code: IPX4 | Night vision distance: 6 m | Height: 107.5 mm | IK code: IK04 | Ethernet LAN: Yes | Number of cameras: 1 | Power consumption (max): 4 W | Ethernet interface type: Fast Ethernet | Wi-Fi: No | Built-in processor: Yes | DC output voltage: 57 | Total megapixels: 4 MP | Sensor type: CMOS | Frame rate: 30 fps | Image quality adjustment:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Contrast | Fixed focus: Yes | LED type: IR | Housing material: Polycarbonate (PC) | Video formats supported: H.264 | Video compression formats: H.264 | Image quality adjustment: Brightness | Image quality adjustment: DNR | Fog proof: Yes | White balance: Manual | Noise reduction: Yes | Screws included: Yes | Night vision: Yes | Placement supported: Indoor & outdoor | Image quality adjustment: Sharpness | Noise reduction technology: 2D noise reduction, 3D noise reduction | Image quality adjustment: Colour depth | Mounting type: Ceiling/Wall/Desk | Built-in HDD: No | Diameter: 4.8 cm | Lens viewing angle, vertical: 54.9° | Lens viewing angle, diagonal: 120.6° | Lens viewing angle, horizontal: 102.4°

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950