Hikvision DS-2CD1161G2-LIU IP camera

Model: DS-2CD1161G2-LIU

Manufacturer: HIKVISION

EAN: 6936422131012

Product Code: 1697798

R2,285

LED type: IR/White | Compatible memory cards: MicroSD (TransFlash) | Housing material: Metal | Web-based management: Yes | Operating relative humidity (H-H): 0 - 95% | Weight: 550 g | Type: IP security camera | Housing material: Plastic | Compatible memory cards: MicroSDHC | Compatible memory cards: MicroSDXC | Operating temperature (T-T): -30 - 60 °C | Minimum illumination: 0 lx | Package width: 150 mm | Depth: 97.6 mm | Power over Ethernet (PoE): Yes | Wide Dynamic Range (WDR): 120 dB | Form factor: Dome | Tilt angle range: 0 - 75° | Ethernet LAN (RJ-45) ports: 1 | Bit rate: 32 Kbps - 16 Mbps | Ethernet LAN: Yes | Storage relative humidity (H-H): 0 - 95% | Maximum resolution: 3200 x 1800 pixels | Package weight: 800 g | International Protection (IP) code: IP67 | Built-in microphone: Yes | Number of cameras: 1 | Highlight Compensation (HLC): Yes | Quality of Service (QoS) support: Yes | Package depth: 150 mm | Storage temperature (T-T): -30 - 60 °C | Product colour: White | Connectivity technology: Wired | Package height: 141 mm | Night vision distance: 30 m | Ethernet LAN data rates: 10,100 Mbit/s | Optical sensor size: 25.4 / 2.4 mm (1 / 2.4") | Total megapixels: 6 MP | Detect distance (wide): 115 m | Maximum aperture number: 1.6 | Region of Interest (ROI) encoding: Yes | Observe distance (wide): 45 m | Camera shutter speed: 1/3 - 1/100000 s | Angle of rotation: 355° | Pan range: 0 - 355° | Progressive scan: Yes | Recognize

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

distance (wide): 23 m | Identify distance (wide): 11 m | Sample rate: 8 kHz / 16 kHz | Diameter: 12.1 cm | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Infra-red wavelength: 850 nm | Noise filter: Yes | Day/night mode: Yes | Signal-to-Noise Ratio (SNR): 52 dB | Sensor type: CMOS | Power management: DC 12 V | Video motion detection: Yes | Mirror: Yes | Video compression formats: H.264 | Video compression formats: H.265 | Video compression formats: H.265+ | Video compression formats: M-JPEG | Video compression formats: H.264+ | Night vision: Yes | Maximum frame rate: 20 fps | Heartbeat: Yes | Maximum memory card size: 512 GB | DC output current: 0.5 A | Number of users: 32 user(s) | Password protection: Yes | Lens viewing angle, diagonal: 127 - 96° | Lens viewing angle, horizontal: 105 - 78° | Lens viewing angle, vertical: 55 - 38° | Sustainability certificates: WEEE | Mono sound: Yes | PoE standard: IEEE 802.3af | Sustainability certificates: REACH

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950