

TP-Link Omada ES208GP network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) DIN rail Black

Model: ES208GP

Manufacturer: TP-LINK

EAN: 1210002609708

Product Code: 1717822

R1,956

MAC address table: 8000 entries | Power source: DC | Jumbo frames support: Yes | Packet buffer memory: 0.5 MB | Rack mounting: Yes | Multicast support: Yes | Depth: 100.7 mm | IGMP snooping: Yes | Operating temperature (T-T): 0 - 40 °C | Operating relative humidity (H-H): 10 - 90% | LED indicators: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Ethernet LAN data rates: 10,100,1000 Mbit/s | Link aggregation: Yes | Web-based management: Yes | Total Power over Ethernet (PoE) budget: 64 W | Loop protection: Yes | Width: 158 mm | Networking

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

standards: IEEE 802.3bt | Storage relative humidity (H-H): 5 - 90% | Power over Ethernet (PoE): Yes | Switch type: Managed | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3at | Virtual LAN features: Port-based VLAN | Virtual LAN features: Tagged VLAN | Input current: 1.31 A | Store-and-forward: Yes | Broadcast storm control: Yes | Virtual LAN features: MTU VLAN | Auto MDI/MDI-X: Yes | Form factor: DIN rail | Number of VLANs: 4000 | Height: 25.4 mm | Flow control support: Yes | Cables included: Power | Product colour: Black | Switch layer: L2 | Power over Ethernet plus (PoE+) ports quantity: 8 | Switching capacity: 16 Gbit/s | Quick start guide: Yes | 10G support: No | Forwarding rate: 11.904 Mpps | DHCP features: DHCP client | Auto-negotiation: Yes | Port mirroring: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Basic switching RJ-45 Ethernet ports quantity: 8 | VLAN support: Yes | Jumbo frames: 15000 | Transmission distance (max): 0.25 km | Cloud-managed: Yes | Power over Ethernet (PoE) type supported: PoE+ | DC input voltage: 53 V | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950