# USL-Motion-3

Model: USL-Motion-3

Manufacturer: UBIQUITI

Product Code: 1723999

# R3,606

## VERSATILE INSTALLATION OPTIONS FOR ANY ENVIRONMENT

The Ubiquiti Motion Sensor offers flexible installation methods, allowing for both adhesive and screw mounting. This adaptability ensures that it can be securely placed in various locations, whether on walls or corners, to maximize its effectiveness. With dimensions of 93.5 x 22.5 x 24.7 mm when wall-mounted and slightly larger for corner mounting, it fits seamlessly into any setting. Its sleek design, made from durable polycarbonate and high-density polyethylene, not only enhances aesthetics but also ensures longevity in diverse environments.

## EXCEPTIONAL BATTERY LIFE AND CONNECTIVITY FEATURES

Designed for efficiency, the Ubiquiti Motion Sensor boasts an impressive battery life of up to 6 years, powered by a CR123A lithium battery. This long-lasting performance minimizes the need for frequent replacements, providing peace of mind and reliability. Connectivity is facilitated through the proprietary SuperLink technology, operating within specific frequency ranges for the US and EU markets. With a maximum power consumption of just 22.6mW, this sensor is energy-efficient, making it an ideal choice for continuous monitoring without the hassle of constant maintenance.

## ADVANCED DETECTION CAPABILITIES WITH PET IMMUNITY

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Equipped with advanced PIR sensor technology, the Ubiquiti Motion Sensor offers a detection range of up to 1.5 meters horizontally and an impressive 6 meters vertically, ensuring comprehensive coverage. The vertical sensor includes pet immunity, allowing it to distinguish between human movement and pets, reducing false alarms. This feature is particularly beneficial for households with animals, ensuring that security measures remain effective without unnecessary interruptions. With an operating temperature range of 0 to 40° C and humidity tolerance of 10 to 90%, this sensor is built to perform reliably in various conditions.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950