GIGABYTE MW34-SP0 Intel W680 LGA 1700 ATX

Model: PLGGIGSIN0024

Manufacturer: GIGABYTE

EAN:

Product Code: 1731857

R9,664

Component for: Server | Motherboard form factor: ATX | DisplayPorts quantity: 1 | Supported storage drive interfaces: M.2, SATA | On-board graphics card model: Aspeed AST2600 | Number of M.2 (M) slots: 4 | RAID levels: 0 | HDMI ports quantity: 1 | Number of SATA connectors: 8 | RAID levels: 5 | Operating relative humidity (H-H): 8 - 80% | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 3 | ATX Power connector (24-pin): Yes | RAID levels: 1 | Motherboard chipset: Intel W680 | RAID levels: 10 | Number of chassis fan connectors: 6 | Package width: 360 mm | Windows operating systems supported: Windows 10 x64 | EPS power connector (8-pin): Yes | Memory channels: Dual-channel | USB 3.2 Gen 1 (3.1 Gen 1) connectors: 1 | RAID support: Yes | Ethernet LAN (RJ-45) ports: 2 | Package depth: 330 mm | TPM connector: Yes | Motherboard chipset family: Intel | Supported storage drive types: HDD & SSD | Cables included: SATA | Front panel connector: Yes | Supported processor sockets: LGA 1700 | Package height: 80 mm | CPU fan connector: Yes | Operating temperature (T-T): 10 - 40 °C | Storage temperature (T-T): -40 - 60 °C | Storage relative humidity (H-H): 20 - 95% | Product colour: Blue | Windows operating systems supported: Windows 11 x64 | Power source type: ATX | LAN controller: Intel I225 | Processor manufacturer: Intel | USB 2.0 connectors: 1 | USB 3.2 Gen

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

2x2 connectors: 1 | 1st M.2 highest PCI Express generation: 4.0 | ECC compatibility: ECC & Non-ECC | Number of CPU fan connectors: 1 | 1st M.2 largest key size: 22110 | Number of EPS power connectors (8-pin): 1 | 2nd M.2 largest key size: 2280 | 3rd M.2 highest PCI Express generation: 4.0 | 4th M.2 highest PCI Express generation: 4.0 | 3rd M.2 largest key size: 2280 | 2nd M.2 highest PCI Express generation: 4.0 | 4th M.2 largest key size: 2280 | Supported memory clock speed (max): 3200 MHz | USB 3.2 Gen 2x2 Type-C ports quantity: 1 | PCI Express x16 (Gen 5.x) slots: 2 | Width: 305 mm | PCI Express x4 slots: 1 | Number of storage drives supported: 12 | Graphics card family: ASPEED | Number of HDDs supported: 8 | Ethernet LAN: Yes | Compatible processor series: Intel Core i7 13th Gen | Compatible processor series: Intel Core i5 12th Gen | Compatible processor series: Intel Core i7 14th Gen | Compatible processor series: Intel Core i7 12th Gen | Compatible processor series: Intel Core i5 14th Gen | Depth: 244 mm | Compatible processor series: Intel Core i9 14th Gen | Compatible processor series: Intel Core i3 12th Gen | Compatible processor series: Intel Core i9 13th Gen | Compatible processor series: Intel Core i5 13th Gen | Compatible processor series: Intel Core i9 12th Gen | Compatible processor series: Intel Core i3 14th Gen | Ethernet interface type: Gigabit Ethernet | Ethernet interface type: 2.5 Gigabit Ethernet | Processor socket: LGA 1700 | Supported memory types: DDR4-SDRAM | Memory slots type: DIMM | Compatible processor series: Intel Core i3 13th Gen | VGA (D-Sub) ports quantity: 1 | Number of memory slots: 4

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950