I/O VIDEO EXTENDER HDMI 1CH 4K/UTP PFM702 DAHUA

Model: PFM702

Manufacturer: DAHUA

EAN: 6937552425149

Product Code: 1737732

R1,781

HDMI extender is used to extend the transmission distance of HDMI signals, resolving the issue of unstable transmission caused by the length limits of HDMI cables (signal degradation typically occurs when cables exceed 15.0 m (49.21 ft)). It enables the long-distance transmission of high-definition signals via various media such as network cables, fiber optics, and wireless connections. Suitable for scenarios such as home theaters, conference rooms, and monitoring displays.

- HDCP 1.4 and DVI 1.0 Compliant
- Supports Video Resolution up to 4K/2K@30 Hz YUV 4:4:4, as Specified in HDMI 1.4
- The Maximum Transmission Distance via a Single CAT6 Shielded Network Cable Is as Follows: 164.04 ft/50.0 m for 1080p, 131.23 ft/40.0 m for 4K@30 Hz
- Supports Copying EDID from Receiver Display or Loop Out Display
- Allows for Cascading via Additional HDMI Loop Out Port
- Supports One-Way PoC Functionality (from Transmitter to Receiver)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

- One-Way IR Signal Transmission
- Compact Design for Easy and Flexible Installation

Summary: Dahua Technology PFM702. Type: AV transmitter & receiver, Maximum resolution: 3840 x 2160 pixels, Cable types supported: Cat6. Connectivity technology: Wired. Power source type: DC, Input current: 1 A, Operating voltage (transmitter): 12 V. Width: 69 mm, Depth: 79.5 mm, Height: 16.5 mm. Quantity per pack: 1 pc(s), Package width: 115 mm, Package depth: 200 mm | Vendor Homepage: https://www.dahuasecurity.com/products/accessories/camera-accessories/video-extensions/pfm702=v1 | Tipas: AV siųstuvas ir imtuvas | Maksimali rezoliucija: 3840 x 2160 | Palaikomi laido tipai: Cat6 | Maksimalus perdavimo atstumas: 50 | Maksimalus atnaujinimo dažnis: 30 | HDCP: Taip | HDCP versija: 1.4 | Medžiaga: Metalas | Produkto spalva: Juoda | Ryšio technologija: Vielinis | Ethernet LAN jungtis: Taip | RJ-45 įvesties prievadai: 2 | HDMI išvesčių skaičius: 2 | HDMI įvestis: 1 | Nuotolinio valdymo (IR) išvestis: 1 | Nuotolinio valdymo (IR) įvestis: 1 | DC įėjimo lizdas: Taip | Maitinimo šaltinio tipas: DC | Darbinė įtampa (siųstuvas): 12 | Įvesties srovė: 1 | Galios suvartojimas (siųstuvas) (maks.): 1.86 | Galios suvartojimas (imtuvas) (maks.): 0.87 | Darbo santykinės drėgmės diapazonas: 20 - 80 | Darbo temperatūros diapazonas (TT): 0 - 40 | Sandėliavimo santykinis drėgmės diapazonas: 5 - 95 | Sandėliavimo temperatūros norma (T-T): -20 - 60 | Plotis: 69 | Ilgis: 79.5 | Aukštis: 16.5 | Svoris: 262 | Kiekis pakuotėje: 1 | Pakuotės plotis: 115 | Pakuotės gylis: 200 | Pakuotės aukštis: 75 | Paketo svoris: 530 | Kintamosios srovės adapteris: Taip | Instrukcija: Taip | Pridedamas IR imtuvas: Taip | Pridedamas IR leistuvas: Taip | Atitikties sertifikatai: CE/RoHS | Kilmės šalis: Kinija | Bruto svoris: 0.53 | Neto svoris: 0.262 | Vienetų skaičius vienoje siuntimo dėžėje: 1 | Name: I/O VIDEO EXTENDER HDMI 1CH 4K/UTP PFM702 DAHUA | Model name: PFM702

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950