Blackview 14 Portable Dual Monitor DCM5

Model: DCM5/BV

Manufacturer: BLACKVIEW

EAN: 6931548327868

Product Code: 1745371

R4,315

Display diagonal: 35.6 cm (14") | Pixel density: 157 ppi | Display resolution: 1920 x 1080 pixels | AC input frequency: 50/60 Hz | Aspect ratio: 16:9 | Supported graphics resolutions: 1920 x 1080 | Tilt angle range: 5 - 20° | Panel type: IPS | Tilt adjustment: Yes | Ethernet LAN: No | HDCP: No | Display technology: LCD | AC input voltage: 100 - 240 V | Height: 207.6 mm | Built-in camera: No | Cables included: 2 x USB Type-C | Number of speakers: 1 | Quick start guide: Yes | Native aspect ratio: 16:9 | Height adjustment: Yes | Weight: 1.53 kg | Screen shape: Flat | Response time: 1 ms | Viewing angle, horizontal: 178° | Display brightness (typical): 300 cd/m² | Product colour: Black | Power consumption (off): 0.3 W | On Screen Display (OSD): Yes | Maximum refresh rate: 200 Hz | HD type: Full HD | LED backlight: Yes | Display diagonal (metric): 60.5 cm | Viewable size, horizontal: 80 cm | HDMI: Yes | HDMI ports quantity: 1 | Microphone in: No | Contrast ratio (typical): 1000:1 | Cables included: USB-C to 2 x USB-A | Width: 357,5 mm | Colour gamut: 100% | Colour depth: 8 bit | Power consumption (max): 310 W | Depth: 27.7 mm | USB Type-C DisplayPort Alternate Mode: No | Operating relative humidity (H-H): 20 - 80% | Display surface: Matt | Power supply type: Internal | Cable lock slot: Yes | Power consumption (standby): 0.5 W | Touchscreen: No | Built-in microphone: No | Feet colour: Black | Operating temperature (T-T): 5 - 35 °C | VESA mounting: Yes | Picture-in-

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Picture: Yes | Market positioning: Office | Operating altitude: 0 - 5000 m | Storage relative humidity (H-H): 20 - 80% | Power consumption (typical): 51 W | Non-operating altitude: 0 - 12192 m | Horizontal scan range: 48 - 180 kHz | Swivelling: Yes | Flicker-free technology: Yes | Display brightness: 300 cd/m² | Viewing angle, vertical: 178° | Viewable size, vertical: 52.7 cm | Display number of colours: 16.7 million colours | Pixel pitch: 0.275 x 0.275 mm | Panel mounting interface: 100 x 100 mm | Built-in USB hub: No | Adjustable height (max): 15 cm | Warnings: Place the monitor on a flat and stable surface to avoid tipping and damage. | Warnings: Do not disassemble the monitor casing to avoid risk of electric shock. | Warnings: Unplug the monitor from the power source before cleaning. | Energy efficiency class (SDR): A | Anti-glare screen: Yes | Low Blue Light technology: Yes | Speaker power: 1.5 W | sRGB coverage (typical): 100% | High Dynamic Range (HDR) technology: DisplayHDR 400 | Detachable stand: Yes | Energy efficiency class (HDR): A | USB Power Delivery (USB PD): No | High Dynamic Range (HDR) supported: Yes | Remotely operated: No | AMD FreeSync type: FreeSync Premium | VESA Adaptive Sync support: Yes | USB connector form factor: 3 x USB-C 3.1 | Energy efficiency scale: A to G | Fast charging: No | Built-in KVM switch: No | Response time measurement type: GTG (Gray to Gray) | European Product Registry for Energy Labelling (EPREL) code: 2653507 | Colour gamut standard: sRGB

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950