Switch MERCUSYS Desktop/pedestal 6x10Base-T 100Base-TX PoE+ ports 4 MS106LP

Model: MS106LP

Manufacturer: MERCUSYS

EAN: 6957939001148

Product Code: 1749294

R919

6-Port 10/100Mbps Desktop Switch with 4-Port PoE+

4 PoE+ Ports (40 W Budget) for Network Deployment

Ports 1-4 support PoE+, and each of them supports a maximum of 30 W and is compliant with the 802.3af/at Powered Devices. MS106LP provides 2 ports without PoE+ for uplink devices, one of which is used to connect to the Internet and the other to connect to the NVR. The total 40 W PoE power budget* for the 4× PoE+ ports enables a variety of uses, including surveillance for offices, dormitories, and small businesses. IP cameras, access points, IP phones, PCs, video recorders, and

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

more are all completely compatible with it.

No Fuss

No need for electricians; simplify installation and deployment.

Cost-Efficiency

Getting rid of extra cables and power adapters will save money on infrastructure.

Flexibility

Deployment in complex situations is made possible by more placement possibilities.

Power Management

Improves power usage while intelligently protecting your gadgets from power surges.

IEEE 802.3af/at

PoE ports compliant with the 802.3af/at Powered Devices.

Traffic Separation

With only one click, isolation mode divides traffic for ports 1-4 to prevent snooping/tampering and isolate broadcast storms for greater protection. MS106LP provides 2× uplink ports when turning on the isolation mode.

Port Prioritization

Prioritizing the data of specific ports would ensure the high quality of delicate applications, such as voice and video, in crucial business domains.

PoE Auto Recovery

The switch continuously detects data transmission with PoE-powered devices (PD). When a PD stops sending data packets to the switch for an extended length of time, the switch will reboot it automatically.

Plug and Play

MS106LP offers auto-negotiation (10/100M) and automated MDI/MDIX. There is no additional

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

configuration needed. It is simple to use and saves time and effort.

Durable and Silent

MS106LP's durable metal case allows for efficient heat dissipation, excellent signal interference prevention, equipment stability, and long network life.

- 6 Ports: 6× 10/100 Mbps RJ45 ports with 4 PoE+ ports
- Two Cables in One: With four PoE+ ports, transfers data and power on one single cable
- High Power PoE+: Support PoE Power up to 30 W for each PoE port and 40 W for all PoE ports*
- 2× Uplink Ports: MS106LP provides 2× uplink ports when turning on the isolation mode. One for connecting to the Internet and one for connecting to the NVR
- Long-Range up to 250 m: Increases PoE transmission distance to 250 m by Extend Mode*
- Isolation Mode: One click to divide traffic for specific ports for stability and security
- Compliant with Powered Devices: Works with IEEE 802.3af/at compliant PDs
- Durable Metal Casing: Allows for efficient heat dissipation and long network life
- Plug and Play: Simple to use and saves time and effort
- PoE Auto Recovery: Automatically reboots your dropped or unresponsive PoE-powered devices

Summary: Mercusys 6-Port 10/100Mbps Desktop Switch with 4-Port PoE+. Switch type: Managed. Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100), Basic switching RJ-45 Ethernet ports quantity: 6. MAC address table: 2000 entries. Networking standards: IEEE 802.3af, IEEE 802.3at, IEEE 802.3x. Power over Ethernet (PoE). Wall mountable | Vendor Homepage: https://www.mercusys.com/en/product/details/ms106lp/ | Perjungimo tipas: Valdomas | Duomenys perduodami į debesies platformą: Taip | Web pagrįstas valdymas: Taip | Eismo klasifikacija: Taip | Pagrindinių perjungimo RJ-45 eterneto prievadų skaičius: 6 | Pagrindinių perjungimo RJ-45 eterneto prievadų tipas: Fast Ethernet (10/100) | Tinklo standartai: IEEE 802.3af/IEEE 802.3at/IEEE 802.3x | 10G parama: Ne | Portų mirroring: Taip | Auto MDI/MDI-X: Taip | Automatinis suderinimas (Auto-negotiation): Taip | Eterneto LAN duomenų perdavimo norma: 10,100 | Srauto kontrolės palaikymas: Taip | Adreso lentelės dydis: 2000 | Stovo montavimas: Ne | Didinimas: Ne | Produkto spalva: Juoda | Montuojamas ant sienos: Taip | Maitinimo šaltinis: AC/DC | Pridėtas maitinimo šaltinis: Taip | AC įėjimo įtampa: 220 | AC įėjimo dažnis: 50 | Energijos suvartojimas: 1.87 | Galios suvartojimas (maks.): 44.8 | Maitinimas per Eternetą (PoE): Taip | Maitinimo per Eternetą (PoE) prievadų skaičius: 4 | Maitinimo per Eternetą plius (PoE+) prievadų skaičius: 2 | Maitinimo per Eternetą (PoE) galia

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

prievadui: 40 | Darbo temperatūros diapazonas (TT): 0 - 40 | Sandėliavimo temperatūros norma (T-T): -40 - 70 | Darbo santykinės drėgmės diapazonas: 10 - 90 | Sandėliavimo santykinis drėgmės diapazonas: 5 - 95 | Šilumos sklaida: 152.32 | Plotis: 99.8 | Ilgis: 98 | Aukštis: 25 | Pridėti kabeliai: AC | Greitos pradžios vadovas: Taip | Bruto svoris: 0.48 | Neto svoris: 0.3 | Vienetų skaičius vienoje siuntimo dėžėje: 1 | Vieneto plotis: 13.5 | Shipping Box Height: 12.5 | Vieneto gylis: 8.5 | Vieneto aukštis: 12.5 | Name: NET SWITCH 6PORT 10/100M/MS106LP MERCUSYS | Model: MS106LP

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950