

**Switch UBIQUITI
USW-Pro-24-PoE
Type L3
Desktop/pedestal
Rack
24x10Base-T
100Base-TX
1000Base-T
2xSFP+ PoE
ports 24 PoE+
ports 16 400
Watts USW-PRO-
24-POE**



Model: USW-PRO-24-POE

Manufacturer: UBIQUITI

EAN: 817882027649

Product Code: 193546

R14,909

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Second-Generation UniFi Switching

We've redesigned our UniFi Switches from the ground up.

Near Silent Cooling

Our new airflow design reduces the need for fan usage.

Powerful Hardware and Software

UniFi Switches offer a variety of features, including 10G SFP+ ports, PoE+ or PoE++ support, and Layer 3* switching capabilities.

Redundant Power System

UniFi SmartPower RPS, USP-RPS, is our PSU failover system.

Power Supply Failure

In the event of a UniFi switch power supply failure, the USP-RPS automatically supplies redundant power to the failed device.

UniFi SmartPower

One UniFi SmartPower device can support up to 6 devices until the failed device is replaced.

Touchscreen Display

The 1.3" touchscreen display allows easy monitoring and quick troubleshooting.

Summary: Ubiquiti UniFi Pro 24-Port PoE. Switch type: Managed, Switch layer: L2/L3. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 24. Full duplex. MAC address table: 16000 entries, Switching capacity: 88 Gbit/s. Networking standards: IEEE 802.3af, IEEE 802.3at. Power connector: AC-in jack. Power over Ethernet (PoE). Rack mounting, Form factor: 1U | Vendor Homepage: <https://switch.ui.com/gen2/> | Quality of Service (QoS) support: Yes | Switch layer: L2/L3 | Switch type: Managed | System event log: Yes | Web-based management: Yes | Basic switching RJ-45 Ethernet ports quantity: 24 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Power connector: AC-in jack | SFP+ module slots quantity: 2 | 10G support: Yes | Broadcast storm control: Yes | Flow control support: Yes | Full duplex: Yes | IPv4 routes: 64 | Link aggregation: Yes | Networking standards: IEEE 802.3af/IEEE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

802.3at | Number of VLANs: 1000 | Port mirroring: Yes | Rate limiting: Yes | VLAN support: Yes | Forwarding rate: 65.472 | Jumbo frames support: Yes | MAC address table: 16000 | Packet buffer memory: 2 | Static route: Yes | Switching capacity: 88 | Throughput: 44000 | Authentication type: IEEE 802.1x,RADIUS | DHCP features: DHCP relay/DHCP server/DHCP snooping | IGMP snooping: Yes | Display type: LCM | Form factor: 1U | LED indicators: Activity/Link/PoE/Speed/System | Product colour: Silver | Rack mounting: Yes | Reset button: Yes | AC input frequency: 50 - 60 | AC input voltage: 100 - 240 | Number of power supply units: 1 | Power consumption (max): 450 | Power source: AC | Power supply included: Yes | Redundant power supply (RPS) support: Yes | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) power per port: 64 | Power over Ethernet 4PPoE (PoE++) ports quantity: 8 | Power over Ethernet plus (PoE+) ports quantity: 16 | Total Power over Ethernet (PoE) budget: 400 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -5 - 40 | Depth: 285.4 | Height: 43.7 | Weight: 4300 | Width: 442.4 | Certification: CE, FCC, IC | Harmonized System (HS) code: 85176990 | Model name: USW-Pro-24-PoE | Units per Shipping Box: 2 | Unit Calculated Volume: 0.03005 | Unit Calculated Weight: 6.5

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950