

## Access Point TP-LINK 22000



**Mbps IEEE**

**802.11a/b/g IEEE**

**802.11n IEEE**

**802.11ac IEEE**

**802.11ax**

**2x10GbE**

**EAP783**

Model: EAP783

Manufacturer: TP-LINK

EAN: 4895252503517

Product Code: 193548

---

## R13,623

---

### Multi-Link Operation (MLO)

Enables devices to simultaneously send and receive data across different frequency bands and channels.

### Two 10G PoE++ Ports

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Boosts overall throughput and offers flexible deployment with two 10 Gbps PoE++ ports.

#### Auto Channel Selection and Power Adjustment

Boost WiFi performance and minimize interference for your network.

#### Intelligent Power Management

Offers more reliable network operation for your business.

#### Centralized Cloud Management

Manage the whole network locally or from the cloud.

#### Omada Mesh Technology

More flexible and convenient wireless deployment.△

#### PoE++ Power

Supports both 12V DC and 802.3bt PoE++ for flexible installations.

- BE19000 Tri-Band Wi-Fi 7: 11520 Mbps (6 GHz) + 5760 Mbps (5 GHz) + 1376 Mbps (2.4 GHz). Buffering will no longer be a problem
- Clear 6 GHz Band: Brings cleaner and wider band resources to your Wi-Fi
- 2× 10G Port: Unlock the full potential of Wi-Fi 7
- 320 MHz Bandwidth: Up to 320 MHz bandwidth enables many more simultaneous transmissions at the fastest possible speeds
- Low Latency and Interference: Multi-Link Operation, and Multi-RUs ensure high performance of your network
- Advanced Functions□ Supports centralized management, mesh, and seamless roaming

Summary: TP-Link Omada BE22000 Ceiling Mount Tri-Band Wi-Fi 7 Access Point. 2.4 GHz, 5 GHz, 6 GHz, Maximum data transfer rate: 19000 Mbit/s. Security algorithms: WPA, WPA2, WPA3. Ethernet LAN data rates: 10000 Mbit/s. Power over Ethernet (PoE). Product colour: White | Vendor Homepage: <https://www.tp-link.com/sg/business-networking/omada-sdn-access-point/eap783/#overview> | 2.4 GHz: Yes | 5 GHz: Yes | 6 GHz: Yes | Airtime Fairness (ATF): Yes | Automatic channel scanning: Yes | Automatic channel selection: Yes | Band steering: Yes | BeamForming: Yes | Ethernet LAN data rates: 10000 | Flow control support: Yes | Frequency band: 2.4 - 6 | Maximum data transfer rate: 19000 |

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950

Maximum data transfer rate (2.4 GHz): 1376 | Maximum data transfer rate (5 GHz): 5760 | Maximum data transfer rate (6 GHz): 11520 | MIMO: Yes | MIMO type: Multi User MIMO | Networking standards: IEEE 802.11a/IEEE 802.11ac/IEEE 802.11ax/IEEE 802.11b/IEEE 802.11be/IEEE 802.11g/IEEE 802.11n | Number of users: 760 | Quality of Service (QoS) support: Yes | Rate limiting: Yes | VLAN support: Yes | Access Control List (ACL): Yes | Security algorithms: WPA/WPA2/WPA3 | DC-in jack: Yes | Ethernet LAN (RJ-45) ports: 2 | DC voltage range: 12 | Power over Ethernet (PoE): Yes | LED indicators: Yes | Placement: Ceiling,Wall | Product colour: White | Reset button: Yes | Antenna type: Internal | Depth: 280 | Height: 46.5 | Width: 280 | Package type: Box | Mounting kit: Yes | Quantity per pack: 1 | Quick start guide: Yes | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): 0 - 40 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -40 - 70 | Model name: EAP783 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.01096 | Unit Calculated Weight: 2.5

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950