

Switch

MIKROTIK Rack

1x10Base-T

100Base-TX

24xSFP+

2xQSFP+ 1xRJ45

CRS326-

24S+2Q+RM



Model: CRS326-24S+2Q+RM

Manufacturer: MIKROTIK

EAN: 4752224002211

Product Code: 193608

R10,546

If you are working with substantial amount of data – like providing Internet access or maintaining a huge data center – this is the perfect upgrade for your setup. CRS326-24S+2Q+RM is our first product with 40 Gbps QSFP+ ports for remarkably fast and stable fiber connection.

Overall it has two 40 Gbps QSFP+ ports and twenty four 10 Gbps SFP+ ports, which provides total nonblocking throughput of 320 Gbps and switching capacity of 640 Gbps with forwarding rate of 252 Mpps with most common packets.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

CRS326-24S+2Q+RM is easy to manage – it has a full size USB port for configuration and dual power supply for redundancy – no unexpected downtime, your clients and colleagues will be thankful!

You can choose between our legendary feature-packed RouterOS for booting or a simpler, but still powerful SwOS. If you would like the ability to use routing and other Layer 3 features in your CRS, use RouterOS

Summary: Mikrotik CRS326-24S+2Q+RM. Switch type: Managed, Switch layer: L3. USB 2.0 ports quantity: 1, Console port: RJ-45. Switching capacity: 640 Gbit/s. Power connector: AC-in jack. Rack mounting, Form factor: 1U | Vendor Homepage:

https://mikrotik.com/product/crs326_24s_2q_rm#fndtn-specifications | Switch layer: L3 | Switch type: Managed | Console port: RJ-45 | Power connector: AC-in jack | QSFP+ module slots quantity: 2 | SFP+ module slots quantity: 24 | USB 2.0 ports quantity: 1 | 10G support: Yes | Forwarding rate: 252 | Switching capacity: 640 | Throughput: 320 | Form factor: 1U | LED indicators: Yes | Product colour: White | Rack mounting: Yes | Reset button: Yes | Built-in processor: Yes | Flash memory: 16 | Internal memory: 64 | Memory type: RAM | Processor frequency: 650 | AC input voltage: 100 - 240 | Power consumption (max): 69 | Redundant power supply (RPS) support: Yes | Power over Ethernet (PoE): No | Operating temperature (T-T): -20 - 60 | Depth: 183 | Height: 44 | Width: 443 | Cables included: AC | Rack mount kit: Yes | Harmonized System (HS) code: 85176990 | Units per Shipping Box: 10 | Unit Calculated Volume: 0.003773 | Unit Calculated Weight: 2.75

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950