

Switch UBIQUITI Pro Max 24 Type L3 USW-PRO- MAX-24



Model: USW-PRO-MAX-24

Manufacturer: UBIQUITI

EAN: 810084692738

Product Code: 193644

R10,244

A 24-port, Layer 3 Etherlighting™ switch with 2.5 GbE.

- Etherlighting™ ports that illuminate to indicate port location, speed/link, and native VLAN/network
- (8) 2.5 GbE RJ45 ports
- (16) GbE RJ45 ports
- (2) 10G SFP+ ports
- DC power backup ready
- Managed with UniFi Network 8.0.24 and later

Summary: Ubiquiti Pro Max 24. Switch layer: L3. Basic switching RJ-45 Ethernet ports type: 2.5G Ethernet (100/1000/2500), Basic switching RJ-45 Ethernet ports quantity: 24. Switching capacity: 112 Gbit/s. Networking standards: IEEE 802.1x. Power connector: AC/DC. Rack mounting, Form factor: 1U | Vendor Homepage: <https://eu.store.ui.com/eu/en/pro/products/usw-pro-max-24> | Switch layer: L3 |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

2.5G Ethernet (copper) ports quantity: 8 | Basic switching RJ-45 Ethernet ports quantity: 24 | Basic switching RJ-45 Ethernet ports type: 2.5G Ethernet (100/1000/2500) | Gigabit Ethernet (copper) ports quantity: 16 | Power connector: AC/DC | SFP+ module slots quantity: 2 | 10G support: Yes | Broadcast storm control: Yes | Flow control support: Yes | Networking standards: IEEE 802.1x | Port mirroring: Yes | Rate limiting: Yes | Virtual LAN features: Voice VLAN | VLAN support: Yes | Jumbo frames support: Yes | Static route: Yes | Switching capacity: 112 | Throughput: 56 | DHCP features: DHCP relay/DHCP snooping | IGMP snooping: Yes | Loop protection: Yes | Display type: LCM | Form factor: 1U | Housing material: SGCC | LED indicators: Link/Network/Speed/Status | Product colour: Grey | Rack mounting: Yes | Reset button: Yes | Stackable: Yes | AC input frequency: 50/60 | AC input voltage: 100 - 240 | Power consumption (max): 50 | Power source: AC/DC | Power supply included: Yes | Redundant power supply (RPS) support: Yes | Power over Ethernet (PoE): No | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -5 - 40 | Depth: 325 | Height: 43.7 | Weight: 4300 | Width: 442.4 | Cables included: Power | Rack mount kit: Yes | Sustainability certificates: CE/Federal Communications Commission (FCC) | Compliance certificates: CE/Federal Communications Commission (FCC)/Industry Canada (IC) | Model: USW-Pro-Max-24 | Model name: Pro Max 24 | Units per Pallet: 0 | Units per Shipping Box: 2 | Unit Calculated Volume: 0.03225 | Unit Calculated Weight: 5.85

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950