

Switch DAHUA CS4228-24GT- 240



Desktop/pedestal Rack 2xSFP 26xRJ45 240 Watts CS4228- 24GT-240

Model: CS4228-24GT-240

Manufacturer: DAHUA

EAN: 6923172571212

Product Code: 193695

R4,848

- Meets the requirements of IEEE802.3,IEEE802.3u,IEEE802.3x,IEEE802.3ab,IEEE802.3z standards
- Meets the requirements of IEEE802.3af, IEEE802.3at, Hi-PoE, and IEEE802.3bt power supply standards
- Manages PoE power consumption and PoE power on/off. Supports Intelligent PoE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

- A wide operating temperature range and a full metal casing that is fully-enclosed and dust-proof

Summary: Dahua Technology CS4228-24GT-240. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 26, Installed SFP modules quantity: 2. MAC address table: 8000 entries, Switching capacity: 56 Gbit/s. Networking standards: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x, IEEE.... Power over Ethernet (PoE). Rack mounting | Vendor Homepage: <https://transmission.dahuasecurity.com/en/product-list/Business/CloudManagementSolution/NetworkSwitch/CS4228-24GT-240> | Cloud-managed: Yes | Switch layer: L2 | Switch type: Managed | Web-based management: Yes | Basic switching RJ-45 Ethernet ports quantity: 26 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Installed SFP modules quantity: 2 | 10G support: No | Flow control support: Yes | Networking standards: IEEE 802.3/IEEE 802.3ab/IEEE 802.3af/IEEE 802.3at/IEEE 802.3bt/IEEE 802.3u/IEEE 802.3x/IEEE 802.3z | Number of VLANs: 32 | Virtual LAN features: Port-based VLAN | VLAN support: Yes | Forwarding rate: 41.66 | Jumbo frames: 15360 | Jumbo frames support: Yes | MAC address table: 8000 | Switching capacity: 56 | DHCP features: DHCP client | Housing material: Steel | Product colour: Black | Rack mounting: Yes | AC input frequency: 47/63 | AC input voltage: 100 - 240 | Input current: 4 | Power consumption (max): 265 | Power source: AC/DC/PoE | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) ports quantity: 24 | Total Power over Ethernet (PoE) budget: 240 | Operating relative humidity (H-H): 5 - 95 | Operating temperature (T-T): -10 - 55 | Storage relative humidity (H-H): 5 - 95 | Storage temperature (T-T): -40 - 70 | Depth: 220 | Height: 44 | Weight: 2500 | Width: 440 | Package depth: 342 | Package height: 90 | Package weight: 3150 | Package width: 540 | Model name: CS4228-24GT-240 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.01652 | Unit Calculated Weight: 3.25

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950