

## **NET ROUTER 1000M 7PORT/RB5009UPR+S+IN MIKROTIK**



Model: RB5009UPR+S+IN

Manufacturer: MIKROTIK

EAN: 4752224007155

Product Code: 193837

## **R5,349**

### **It's all about the power...**

This version of the RB5009 has all the bells and whistles of the previous model: Gigabit Ethernet, 2.5 Gigabit Ethernet, and a 10 Gigabit SFP+ cage for fiber connectivity. It has the speed, the power, and the durability. But this time, we have added PoE-in & PoE-out on all eight Ethernet ports. Combined with the 2-pin connector and the DC jack, you're getting 10 separate ways of powering. Dual redundant power supplies would usually take your uninterrupted uptime to the next level. RB5009UPr+S+IN takes it one step above that!

All power options support a wide voltage range of 24 - 57 V. However, you can not mix the voltages. If you're using PoE-out to power other devices, the board will choose the source with the highest voltage (DC jack or the 2-pin connector) to power those.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Each PoE-out port can supply up to 25W of power. All the ports combined are limited to 130W, which should be enough for most setups. You can specify maximum available power from your power sources manually, if necessary. When it comes to PoE-out features, the new RB5009 can trade blows with our legendary PoE switches: CRS354 & CRS328. In the smallest possible form-factor and for the best price on the market!

Protect your uptime, protect your tranquility!

So what exactly happens if there is a problem with one of your power sources? Here's a quick example: you have 24V on the DC jack, 48V on the 2-pin connector, and 57V on the PoE-in. The board itself gets powered by the highest voltage input – the PoE-in. If there's a problem, RB5009 will fall back to the second highest voltage – the 2-pin connector. And if that fails – there's the 24V option on the DC jack.

What about the PoE-out devices? Once again – the highest voltage wins. PoE-out devices will draw power from the 48V source on the 2-pin connector. If that fails – the 24V on the DC jack come into play. The board will always reserve 20 watts to power itself. If there is not enough power for all the PoE-out ports, it will start disabling the ones with the lowest priority. You can set the port priority manually.

This tiny form-factor shines anywhere: from confined research facilities and offices to huge corporate server rooms. And don't forget that you can mount FOUR of these routers in a single 1U rackmount space

With the new RB5009, we want to empower all the small and medium ISPs that are always on the lookout for the most cost-effective and robust solutions. It is a perfect addition to our previous GPEN devices – a line of products designed to replace the expensive GPON solutions.

With so many powering options and a durable metallic case, the new RB5009 redefines affordable reliability.

Summary: Mikrotik RB5009UPR+S+IN. Networking standards: IEEE 802.3af, IEEE 802.3at, Ethernet interface type: 2.5 Gigabit Ethernet, Gigabit Ethernet, Cabling technology: 10/100/1000Base-T(X). USB version: 3.2 Gen 1 (3.1 Gen 1). Processor model: 88F7040, Processor frequency: 350 MHz,

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950

Internal storage capacity: 1 GB. Product colour: Black. Power consumption (typical): 150 W, Power source type: PoE | Vendor Homepage: [https://mikrotik.com/product/rb5009upr\\_s\\_in#fndtn-specifications](https://mikrotik.com/product/rb5009upr_s_in#fndtn-specifications) | 3G/4G USB modem compatibility: No | DSL WAN: No | Ethernet WAN: No | SFP WAN: No | SIM card slot: No | Cabling technology: 10/100/1000Base-T(X) | Ethernet interface type: 2.5 Gigabit Ethernet/Gigabit Ethernet | Networking standards: IEEE 802.3af/IEEE 802.3at | DC-in jack: Yes | Ethernet LAN (RJ-45) ports: 8 | Power over Ethernet (PoE) ports quantity: 8 | SFP+ module slots quantity: 1 | USB ports quantity: 1 | USB version: 3.2 Gen 1 (3.1 Gen 1) | Manual: Yes | Certification: CE, EAC, ROHS | Internal memory: 1024 | Internal storage capacity: 1 | Operating system installed: RouterOS | Processor frequency: 350 | Processor model: 88F7040 | Temperature monitoring: Yes | Voltage monitoring: Yes | Product colour: Black | Power consumption (typical): 150 | Power over Ethernet (PoE): Yes | Power source type: PoE | Operating temperature (T-T): -40 - 60 | Model: RB5009UPr+S+IN | Units per Pallet: 0 | Units per Shipping Box: 10 | Unit Calculated Volume: 0.003432 | Unit Calculated Weight: 1.32

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950