

Switch UBIQUITI USW-24 Type L2 24x10Base-T 100Base-TX 1000Base-T 1xSFP USW-24



Model: USW-24

Manufacturer: UBIQUITI

EAN: 810010071385

Product Code: 193872

R5,208

UniFi Switch 24 is a fully managed Layer 2 switch with (24) Gigabit Ethernet ports and (2) Gigabit SFP ports for fiber connectivity

The USW-24 is a configurable Layer 2 switch with 24 Gigabit Ethernet ports and 2 SFP ports. The SFP ports provide 1 Gbps fiber uplink options to your enterprise network. The USW-24 features a 1.3" touchscreen, compact size, and fanless design. The touchscreen displays the current switch state and information for quick diagnosis. Managed and configured by the UniFi Network application with UniFi mobile app support, the USW-24 switch offers an extensive suite of advanced Layer 2 switching protocols and features, including operating mode (switching, mirroring, or aggregate) per port.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

- (24) Gigabit Ethernet Ports
- (2) Gigabit SFP Ports
- 1.3" color touchscreen for status information
- Managed with UniFi Network application
- 1U rackmountable (kit included)

Summary: Ubiquiti UniFi USW-24. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 24. Networking standards: IEEE 802.3af, IEEE 802.3at. Power connector: AC-in jack. Rack mounting | Vendor Homepage: <https://dl.ubnt.com/> | Switch layer: L2 | Switch type: Managed | Web-based management: Yes | Basic switching RJ-45 Ethernet ports quantity: 24 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Power connector: AC-in jack | SFP module slots quantity: 2 | 10G support: No | Ethernet LAN data rates: 10,100,1000 | Networking standards: IEEE 802.3af/IEEE 802.3at | Product colour: Silver | Rack mounting: Yes | Stackable: Yes | AC input frequency: 50 - 60 | AC input voltage: 100 - 240 | Power consumption (typical): 120 | Power source: AC | Power supply included: Yes | Power over Ethernet (PoE): No | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -5 - 40 | Depth: 200 | Height: 43.7 | Weight: 2700 | Width: 442.4 | Certification: CE, FCC, IC | Harmonized System (HS) code: 85176990 | Model name: USW-24 | Units per Pallet: 18 | Units per Shipping Box: 2 | Unit Calculated Volume: 0.02387 | Unit Calculated Weight: 4.25

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950