

Switch MIKROTIK CRS310- 8G+2S+IN 1 2 CRS310- 8G+2S+IN



Model: CRS310-8G+2S+IN

Manufacturer: MIKROTIK

EAN: 4752224008367

Product Code: 193951

R3,981

The world of networking is on the move. Even small offices are shifting from Gigabit connections to the lightning-fast realm of 2.5 Gigabit connectivity. With CRS310-8G+2S+IN, we aim to give you the tools to outpace your competition with a strong combination of eight 2.5 Gigabit Ethernet ports and two 10 Gigabit SFP+ ports in a compact, powerful package! Furthermore, these SFP+ cages support multiple data rates: 1G, 2.5G, and 10G. So you can use this switch as a 10x 2.5G switch, if needed. Classic MikroTik flexibility!

The amazing Marvell 98DX226S switch-chip and integrated dual-core ARM CPU can handle the full potential of RouterOS v7. Run VLANs, Jumbo frames, link aggregation, ACL rules, and so much more! You can even do some hardware offloaded Layer-3 routing.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

There are multiple mounting options. You can easily install the CRS310-8G+2S+IN in a standard 19" rack using the provided rackmount ears. Another option is to get the RMK-2/10 accessory set, which allows you to mount two CRS310 units within the same 1U 19" rack space or mount it in a 10" rack. The choice is yours!

Summary: Mikrotik CRS310-8G+2S+IN: L3 Smart Switch. Switch type: Managed, Switch layer: L3. Basic switching RJ-45 Ethernet ports type: 2.5G Ethernet (100/1000/2500), Basic switching RJ-45 Ethernet ports quantity: 8. DC input voltage: 18 - 57 V. Rack mounting, Form factor: 1U | Vendor Homepage: https://mikrotik.com/product/crs310_8g_2s_in#fndtn-downloads | Switch layer: L3 | Switch type: Managed | Basic switching RJ-45 Ethernet ports quantity: 8 | Basic switching RJ-45 Ethernet ports type: 2.5G Ethernet (100/1000/2500) | SFP+ module slots quantity: 2 | USB Type-A ports quantity: 1 | 10G support: Yes | Form factor: 1U | International Protection (IP) code: IP20 | Number of fans: 1 | Product colour: White | Rack mounting: Yes | Built-in processor: Yes | Flash memory: 32 | Internal memory: 256 | Mean time between failures (MTBF): 200000 | Operating system installed: RouterOS | Processor frequency: 800 | Processor model: 98DX226S | DC input voltage: 18 - 57 | Power consumption (max): 34 | Power source: DC | Power supply included: Yes | Power over Ethernet (PoE): No | Operating temperature (T-T): -40 - 60 | Depth: 206.1 | Height: 44 | Width: 200 | Certification: CE, EAC, ROHS | Model name: CRS310-8G+2S+IN | Units per Shipping Box: 6 | Unit Calculated Volume: 0.006253 | Unit Calculated Weight: 1.42

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950