

NET ROUTER/SWITCH 8PORT 1000M/4SFP CRS112-8P-4S- IN MIKROTIK



Model: CRS112-8P-4S-IN

Manufacturer: MIKROTIK

EAN: 4752224002105

Product Code: 193960

R3,909

CRS112-8P-4S-IN is an eight Gigabit RJ45 port PoE switch, that offers different power output options: autosensing 802.3af/at PoE/PoE+ and Passive PoE, and four SFP ports provide optical fiber connectivity options to support uplinks of up to 1 Gbps.

CRS112-8P-4S-IN is equipped with 12 independent switching ports. 28 V 3.4 A power supply is already included in the box. There is secondary DC jack on the back of the enclosure that supports 48-57 V power supply (not included, can be purchased separately). CRS112-8P-4S-IN can power 802.3af/at devices if 48-57 V DC input is used (unit will automatically detect and provide correct power to devices). Max current is 1 A per port if input voltage is 18-28 V, 450 mA if 48-57 V. Total limit is 2.8A@24V and 1.4A@48-57V. PoE-Out is passed over mode B 4,5 (+) and 7,8 (-) pins

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Summary: Mikrotik CRS112-8P-4S-IN. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 8. Networking standards: IEEE 802.3af, IEEE 802.3at. DC input voltage: 18 - 57 V. Power connector: DC-in jack. Power over Ethernet (PoE) | Vendor Homepage: https://mikrotik.com/product/crs112_8p_4s_in#fndtn-downloads | Basic switching RJ-45 Ethernet ports quantity: 8 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Power connector: DC-in jack | SFP module slots quantity: 4 | 10G support: No | Networking standards: IEEE 802.3af/IEEE 802.3at | Product colour: White | Built-in processor: Yes | Compatible operating systems: RouterOS L5 | Flash memory: 16 | Internal memory: 128 | Processor frequency: 400 | DC input voltage: 18 - 57 | Power consumption (max): 10 | Power over Ethernet (PoE): Yes | Operating temperature (T-T): -20 - 60 | AC adapter included: Yes | Harmonized System (HS) code: 85176990 | Model: MIKROTIK 4SFP CRS112-8P-4S-IN | Units per Shipping Box: 10 | Unit Calculated Volume: 0.005392 | Unit Calculated Weight: 1.62

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950