

Access Point MIKROTIK 1167 Mbit/s 2xLAN ports WAPGR- 5HACD2HND&R11E- LTE6



Model: WAPGR-5HACD2HND&R11E-LTE6

Manufacturer: MIKROTIK

EAN: 4752224004925

Product Code: 193975

R3,830

A small package with huge ambition – the WAP ac LTE6 kit is an upgrade of our extremely cost-effective dual-band (2.4 / 5 GHz) home access point based on the popular weatherproof WAP form factor. Its new CAT6 LTE modem enables even greater download speed – up to 300 Mbps!

CAT6 also enables carrier aggregation and allows the device to use multiple bands at the same time. A huge advantage when there are a lot of LTE users in the area. It provides better responsiveness in a crowded environment and higher efficiency for weaker signal situations in the countryside.

WAP ac LTE6 kit has two Gigabit Ethernet ports – you can use the device as a wired router with LTE backup via the Micro SIM slot. Alternatively, you can enjoy smooth wireless experience anywhere –

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

indoors or outdoors. wAP ac LTE is designed to deliver strong and reliable connection in almost any situation and weather conditions. It can withstand temperatures from -30 C° to +60 C° and can be easily mounted on walls, ceilings or poles.

Summary: Mikrotik wAP ac LTE6 kit. 2.4 GHz, 5 GHz, Maximum data transfer rate: 1167 Mbit/s, Ethernet LAN data rates: 10,100,1000 Mbit/s. Power over Ethernet (PoE). Product colour: White.

Power consumption (max): 16 W | Vendor Homepage:

https://mikrotik.com/product/wap_ac_lte6_kit#fndtn-specifications | 2.4 GHz: Yes | 5 GHz: Yes | Ethernet LAN data rates: 10/100/1000 | Maximum data transfer rate: 1167 | Maximum data transfer rate (2.4 GHz): 300 | Maximum data transfer rate (5 GHz): 867 | DC-in jack: Yes | Ethernet LAN (RJ-45) ports: 2 | AC input voltage: 10 - 57 | Power consumption (max): 16 | Power over Ethernet (PoE): Yes | Product colour: White | Antenna direction type: Omni-directional | Antenna gain level (max): 4 | Antenna type: Internal | Built-in processor: Yes | Flash memory: 128 | Internal memory: 16 | Operating system installed: RouterOS | Processor frequency: 716 | Certification: CE/RED, FCC, IC, EAC, ROHS | AC adapter included: Yes | Mounting kit: Yes | PoE adapter included: Yes | Operating temperature (T-T): -30 - 60 | Harmonized System (HS) code: 85176990 | Model name: wAP ac LTE6 kit // RBwAPGR-5HacD2HnD&R11e-LTE6 | Units per Shipping Box: 20 | Unit Calculated Volume: 0.003106 | Unit Calculated Weight: 0.83

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950