

WRL ROUTER LTE CAT 4/RUT241 TELTONIKA



Model: RUT241

Manufacturer: TELTONIKA

EAN: 4779051840151

Product Code: 193979

R3,808

// RUT241 is the modified version of our all-time bestseller RUT240 that inherited its' best features, including industrial design, compact size, multiple connection interfaces, and compatibility with RMS.

// Equipped with 4G LTE, Wi-Fi, and two Ethernet ports, this router offers unstoppable connection continuity with a backup through automatic failover.

// Digital Inputs and Outputs coupled with advanced RutOS software enable solution automation scenarios.

// RUT241 is an excellent fit in various IoT and M2M solutions that require easy setup, reliable network, and remote accessibility.

- 4G (LTE-FDD): B1, B3, B7, B8, B20, B28A

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

- 3G: B1, B8
- 2G: B3, B8

Summary: Teltonika RUT241. Device type: Cellular network router, Product colour: Black, Housing material: Aluminium, Plastic. Ethernet LAN interface type: Fast Ethernet, Ethernet LAN data rates: 10,100 Mbit/s, Networking standards: IEEE 802.3, IEEE 802.3u. Wi-Fi standards: 802.11b, 802.11g, Wi-Fi 4 (802.11n). Data network: 2G, 3G, 4G, 4G standard: LTE, 2G bands supported: 900,1800 MHz. Security algorithms: HTTPS, SSH, SSL/TLS, WEP, WPA-EAP, WPA-PSK, WPA2-Enterprise, WPA2-PSK | Vendor Homepage: <https://teltonika-networks.com/product/rut241/> | Built-in display: No | Device type: Cellular network router | Housing material: Aluminium/Plastic | LED indicators: Yes | Market positioning: Industrial | Mounting: DIN-rail | Product colour: Black | Reset button: Yes | Auto MDI/MDI-X: Yes | Ethernet LAN: Yes | Ethernet LAN data rates: 10/100 | Ethernet LAN interface type: Fast Ethernet | Networking standards: IEEE 802.3/IEEE 802.3u | Wi-Fi: Yes | Wi-Fi standards: 802.11b/802.11g/Wi-Fi 4 (802.11n) | 2G bands supported: 900,1800 | 3G bands supported: 2100/850/900 | 4G bands supported: 2300/2500/2600 | 4G standard: LTE | Data network: 2G/3G/4G | Number of SIM cards: 1 | Short Message Service (SMS): Yes | Ethernet LAN (RJ-45) ports: 1 | DMZ support: Yes | Firewall: Yes | Network address translation (NAT): Yes | Port forwarding: Yes | Security algorithms: HTTPS/SSH/SSL/TLS/WEP/WPA2-Enterprise/WPA2-PSK/WPA-EAP/WPA-PSK | Antenna connector type: SMA | Antenna type: External | Antennas quantity: 3 | Built-in processor: Yes | Processor frequency: 0.58 | RAM capacity: 0.128 | Web-based management: Yes | Output voltage: 9 - 30 | Power source type: DC | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -40 - 75 | Depth: 74 | Height: 25 | Weight: 125 | Width: 83 | Harmonized System (HS) code: 85176990 | Model: RUT241 | Model name: RUT241010000 | Units per Pallet: 0 | Units per Shipping Box: 10 | Unit Calculated Volume: 0.002317 | Unit Calculated Weight: 0.446

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950