

## Switch TELTONIKA TSW202000000 Type L2 PoE+ ports 8 240 Watts TSW202



Model: TSW202

Manufacturer: TELTONIKA

EAN: 4779051840281

Product Code: 194080

## R3,117

TSW202 is the first-ever managed industrial switch from Teltonika Networks, giving you greater control over how data flows through your network and the role its ports perform in your solution. Define their settings, routing, port mirroring, and more with simplicity and ease.

PoE+ with 30 W max power per port and 240 W total PSE makes the TSW202 centralize your power supply. PoE Management gives you more control over the power distribution of your solution, letting you turn PoE on or off on selected ports.

The switch is equipped with 8 Gigabit Ethernet VLAN ports, allowing for management, configuration,

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

and monitoring of your network. Additional software features like QoS enhance effective bandwidth management and network traffic classifying and prioritizing.

Designed for industrial environments, the TSW202 features an integrated DIN rail bracket, rugged aluminum housing, and extreme temperature and vibration resistance for maximum durability with ease of installation.

- MANAGED SWITCH
- PoE+
- SFP
- GIGABIT ETHERNET

Summary: Teltonika TSW202. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 8, Installed SFP modules quantity: 2. Full duplex. MAC address table: 8000 entries, Switching capacity: 20 Gbit/s. Networking standards: IEEE 802.1p, IEEE 802.3af, IEEE 802.3at, IEEE 802.3z. Power connector: Terminal block (3-pin). Power over Ethernet (PoE) | Vendor Homepage: [teltonika-networks.com/products/ethernet-switches/tsw202](http://teltonika-networks.com/products/ethernet-switches/tsw202) | Quality of Service (QoS) support: Yes | Switch layer: L2 | Switch type: Managed | Web-based management: Yes | Basic switching RJ-45 Ethernet ports quantity: 8 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Gigabit Ethernet (copper) ports quantity: 8 | Installed SFP modules quantity: 2 | Power connector: Terminal block (3-pin) | 10G support: No | Active link detection: Yes | Auto-negotiation: Yes | Full duplex: Yes | Link aggregation: Yes | Networking standards: IEEE 802.1p/IEEE 802.3af/IEEE 802.3at/IEEE 802.3z | Port mirroring: Yes | VLAN support: Yes | Jumbo frames: 10000 | Jumbo frames support: Yes | MAC address table: 8000 | Switching capacity: 20 | DHCP features: DHCP client | IGMP snooping: Yes | DIN rail mounting: Yes | Housing material: Aluminium | International Protection (IP) code: IP30 | LED indicators: Power/Status | Product colour: Aluminium/Blue | Rack mounting: No | Reset button: Yes | Stackable: No | Power supply included: No | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) ports quantity: 8 | Power over Ethernet (PoE) power per port: 30 | Power over Ethernet (PoE) type supported: Active PoE | Total Power over Ethernet (PoE) budget: 240 | Operating temperature (T-T): -40 - 75 | Depth: 44.2 | Height: 122 | Weight: 610 | Width: 132 | Model: TSW202 | Model name: TSW202000000 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.0009112 | Unit Calculated Weight: 0.64

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950