

Switch DAHUA CS4010-8GT-110 Type L2 Desktop/pedestal 8x10Base-T 100Base-TX 1000Base-T PoE ports 8 DH- CS4010-8GT-110



Model: DH-CS4010-8GT-110

Manufacturer: DAHUA

EAN: 6923172571151

Product Code: 194100

R1,883

- Meets the requirements of IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab standards
- Meets the requirements of IEEE802.3af, IEEE802.3at, Hi-PoE, and IEEE802.3bt power supply standards
- Manages PoE power consumption and PoE power on/off. Supports Intelligent PoE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

- A wide operating temperature range and a full metal casing that is fully-enclosed and dust-proof

Summary: Dahua Technology DH-CS4010-8GT-110. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 10. MAC address table: 8000 entries, Switching capacity: 20 Gbit/s. Networking standards: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x. DC input voltage: 54 V. Power over Ethernet (PoE) | Vendor Homepage: <https://www.dahuasecurity.com/products/All-Products/Transmission/Cloud-Managed-Switches/CS4010-8GT-110> | Cloud-managed: Yes | Quality of Service (QoS) support: Yes | Switch layer: L2 | Switch type: Managed | Web-based management: Yes | Basic switching RJ-45 Ethernet ports quantity: 10 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Gigabit Ethernet (copper) ports quantity: 10 | 10G support: No | Copper ethernet cabling technology: 1000BASE-T/100BASE-TX/10BASE-T | Ethernet LAN data rates: 10,100,1000 | Flow control support: Yes | Networking standards: IEEE 802.3/IEEE 802.3ab/IEEE 802.3af/IEEE 802.3at/IEEE 802.3bt/IEEE 802.3u/IEEE 802.3x | Number of VLANs: 32 | Spanning tree protocol: Yes | Virtual LAN features: Port-based VLAN | VLAN support: Yes | Forwarding rate: 4.17 | Jumbo frames: 15000 | Jumbo frames support: Yes | MAC address table: 8000 | Packet buffer memory: 0.5 | Switching capacity: 20 | DHCP features: DHCP client | Housing material: Metal | LED indicators: Yes | Product colour: Black | Rack mounting: No | Reset button: Yes | DC input voltage: 54 | Input current: 2.22 | Power consumption (max): 110 | Power source: DC/PoE | Power supply included: Yes | Redundant power supply (RPS) support: Yes | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) ports quantity: 8 | Operating relative humidity (H-H): 5 - 95 | Operating temperature (T-T): -10 - 55 | Storage relative humidity (H-H): 5 - 95 | Storage temperature (T-T): -40 - 70 | Depth: 106 | Height: 30 | Weight: 550 | Width: 190 | Package depth: 244 | Package height: 87 | Package weight: 1300 | Package width: 256 | Sustainability compliance: Yes | Compliance certificates: CE | Model name: CS4010-8GT-110 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.005623 | Unit Calculated Weight: 1.28

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950