

Switch TP-LINK
Switch type
Unmanaged
Stackable Yes
16xRJ-45 ports
RJ-45 Ports Type
Gigabit Ethernet
(10/100/1000)
16xGigabit
Ethernet
(copper) ports
quantity Power
over Ethernet
(PoE) Yes TL-
SG116P



Model: TL-SG116P

Manufacturer: TP-LINK

EAN: 4895252500301

Product Code: 194148

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

R2,537

NET SWITCH 16PORT 1000M POE+/TL-SG116P TP-LINK

- With 16 PoE+ ports, transfers data and power on one single cable
- Compliance with IEEE 802.3af/at PoE+, the switch supports PoE Power up to 30 W for each PoE port
- Supports PoE Power up to 120 W for all PoE ports*
- Up to 250 m data and power transmission range under Extend Mode**
- Priority Mode ensures high priority of ports 1-4 to guarantee the quality of the sensitive applications
- Isolation Mode allows one-click client traffic separation for higher security and performance
- Automatically reboots your dropped or unresponsive PoE-powered devices with PoE Auto Recovery
- Plug and play with no configuration required

Summary: TP-Link 16-Port Gigabit Desktop Switch with 16-Port PoE+. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 16. Full duplex. MAC address table: 8000 entries, Switching capacity: 32 Gbit/s. Networking standards: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u. DC input voltage: 9 V. Power over Ethernet (PoE). Wall mountable | Vendor Homepage: <https://www.tp-link.com/au/business-networking/unmanaged-switch/tl-sg116p/> | Quality of Service (QoS) support: Yes | Switch type: Unmanaged | Basic switching RJ-45 Ethernet ports quantity: 16 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Gigabit Ethernet (copper) ports quantity: 16 | Auto MDI/MDI-X: Yes | Auto-negotiation: Yes | Broadcast storm control: Yes | Cable length detection: Yes | Cable types supported: Cat3/Cat4/Cat5/Cat5e/Cat6 | Copper ethernet cabling technology: 1000BASE-T/100BASE-TX/10BASE-T | Flow control support: Yes | Full duplex: Yes | Link aggregation: Yes | Networking standards: IEEE 802.1p/IEEE 802.1Q/IEEE 802.3/IEEE 802.3ab/IEEE 802.3u | Number of VLANs: 32 | Port mirroring: Yes | Rate limiting: Yes | Virtual LAN features: Protocol-based VLAN/Tagged VLAN | VLAN support: Yes | Forwarding rate: 23.81 | Jumbo frames:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

9000 | Jumbo frames support: Yes | MAC address table: 8000 | Number of queues: 4 | Packet buffer memory: 4.1 | Store-and-forward: Yes | Switching capacity: 32 | IGMP snooping: Yes | Loop protection: Yes | Housing material: Metal | LED indicators: Yes | Product colour: Black | Stackable: Yes | Wall mountable: Yes | AC input frequency: 50 | AC input voltage: 220 | DC input voltage: 9 | Input current: 0.6 | Power consumption (max): 144.28 | Power consumption (typical): 11.72 | Power supply included: Yes | Power over Ethernet (PoE): Yes | Heat dissipation: 490.55 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): 0 - 40 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -40 - 70 | Depth: 111.7 | Height: 25.4 | Width: 286 | Quick start guide: Yes | Package depth: 434 | Package height: 70 | Package weight: 2000 | Package width: 227 | Model: TL-SG116P | Units per Shipping Box: 1 | Unit Calculated Volume: 0.007004 | Unit Calculated Weight: 2.01

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950