



**Switch**  
**MIKROTIK**  
**CSS610-8G-**  
**2S+IN**  
**Desktop/pedestal**  
**8x10Base-T**  
**100Base-TX**  
**1000Base-T**  
**2xSFP+ CSS610-**  
**8G-2S+IN**

Model: CSS610-8G-2S+IN

Manufacturer: MIKROTIK

EAN: 4752224006929

Product Code: 194221

**R2,248**

Eight 1G Ethernet ports and two SFP+ ports for 10G fiber connectivity. Portable, powerful and extremely cost-effective - this switch is an instant classic!

Cloud Smart Switch 610-8G-2S+IN is our answer to the everlasting demand for more power in a

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

small and simple package. It comes with the lightweight SwOS which is easy to configure from your web browser. It gives you all the basic functionality for a managed switch, and more: you can manage port-to-port forwarding, broadcast storm control, apply MAC filters, configure VLANs, mirror traffic, apply bandwidth limitation and even adjust some MAC and IP header fields.

Summary: Mikrotik CSS610-8G-2S+IN. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 8. DC input voltage: 12 - 57 V. Power over Ethernet (PoE) | Vendor Homepage: [https://mikrotik.com/product/css610\\_8g\\_2s\\_in#fndtn-specifications](https://mikrotik.com/product/css610_8g_2s_in#fndtn-specifications) | Basic switching RJ-45 Ethernet ports quantity: 8 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | SFP+ module slots quantity: 2 | 10G support: Yes | International Protection (IP) code: IP20 | LED indicators: Yes | Product colour: White | Internal memory: 0.64 | Mean time between failures (MTBF): 200000 | Memory type: Flash | Operating system installed: SwitchOS Lite | DC input voltage: 12 - 57 | Power consumption (max): 11 | Power source: DC/PoE | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) type supported: Passive PoE | Operating temperature (T-T): -20 - 60 | Depth: 167 | Height: 46 | Width: 200 | Model name: CSS610-8G-2S+IN | Units per Pallet: 0 | Units per Shipping Box: 10 | Unit Calculated Volume: 0.004586 | Unit Calculated Weight: 1.02

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950