

Switch DAHUA CS4006-4GT-60 Type L2 Desktop/pedestal PoE ports 4 60 Watts DH- CS4006-4GT-60



Model: DH-CS4006-4GT-60

Manufacturer: DAHUA

EAN: 6923172571144

Product Code: 194355

R1,017

Highly intuitive, the Smart Managed Switch can manage local networks. With the DoLynk Care platform, it can also perform cloud management. The switch performs operation and maintenance using topology visualization on front-end, transmission and back-end storage devices that are in the security system and IT system. With its full metal design, the switch has great heat dissipation and can operate in temperatures ranging -10°C to 55°C. It offers EMC and has protection against overvoltage, overcurrent, static electricity, lightning strikes, pulses and other types of interference. For the PoE series Smart Managed Switch, power is supplied up to 250 meters away. The orange port supplies up to 60 W and the red port provides up to 90 W. Also, link aggregation and STP are

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

available on select models to ensure

the network remains stable. The switch can be used in small and medium-sized businesses such as supermarkets, offices, restaurants, cafés and hotels.

- Meets the requirements of IEEE802.3,IEEE802.3u,IEEE802.3x,IEEE802.3ab standards
- Meets the requirements of IEEE802.3af, IEEE802.3at, Hi-PoE power supply standards
- Manages PoE power consumption and PoE power on/off. Supports Intelligent PoE
- A wide operating temperature range and a full metal casing that is fully-enclosed and dust-proof

Summary: Dahua Technology DH-CS4006-4GT-60. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 6. Full duplex. MAC address table: 8000 entries, Switching capacity: 12 Gbit/s. Networking standards: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x. DC input voltage: 53 V. Power over Ethernet (PoE). Wall mountable | Vendor Homepage: <https://www.dahuasecurity.com/products/All-Products/Transmission/Cloud-Managed-Switches/CS4006-4GT-60> | Cloud-managed: Yes | Quality of Service (QoS) support: Yes | Switch layer: L2 | Switch type: Managed | Web-based management: Yes | Basic switching RJ-45 Ethernet ports quantity: 6 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Gigabit Ethernet (copper) ports quantity: 6 | 10G support: No | Copper ethernet cabling technology: 1000BASE-T/100BASE-TX/10BASE-T | Ethernet LAN data rates: 10,100,1000 | Flow control support: Yes | Full duplex: Yes | Link aggregation: Yes | Networking standards: IEEE 802.3/IEEE 802.3ab/IEEE 802.3af/IEEE 802.3at/IEEE 802.3u/IEEE 802.3x | Number of VLANs: 32 | Spanning tree protocol: Yes | Virtual LAN features: Port-based VLAN | VLAN support: Yes | Forwarding rate: 8.93 | Jumbo frames: 15000 | Jumbo frames support: Yes | MAC address table: 8000 | Switching capacity: 12 | DHCP features: DHCP client | Housing material: Metal | LED indicators: Yes | Product colour: Black | Reset button: Yes | Wall mountable: Yes | DC input voltage: 53 | Input current: 1.226 | Power consumption (max): 65 | Power source: DC | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) ports quantity: 4 | Operating relative humidity (H-H): 5 - 95 | Operating temperature (T-T): -10 - 55 | Storage relative humidity (H-H): 5 - 95 | Storage temperature (T-T): -40 - 70 | Depth: 90 | Height: 26 | Weight: 290 | Width: 130 | Package depth: 238 | Package height: 76 | Package weight: 940 | Package width: 265 | Model name: DH-CS4006-4GT-60 | Units per Pallet: 0 | Units per Shipping Box: 12 | Unit Calculated Volume: 0.002527 | Unit Calculated Weight: 0.783

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950