

Access Point MIKROTIK IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac RBCAPGI- 5ACD2ND



Model: RBCAPGI-5ACD2ND

Manufacturer: MIKROTIK

EAN: 4752224003416

Product Code: 194367

R1,623

The cAP ac is a very capable and powerful wireless access point that looks beautiful on both walls and ceilings. The concurrent dual band wireless radio supports dual chain 2 GHz 802.11b/g/n and 5 GHz in a/n/ac standards, and will provide coverage in 360 degrees around it.

Even though the radio supports repeater mode, the two Ethernet ports give you the ability to extend your network with cables, even if PoE power is required, since the cAP ac supports 802.3af/at PoE input on the first port, and passive PoE output on the second port. Device supports IPsec hardware

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

acceleration too.

The cAP ac is a feature packed device with a sleek enclosure, that can become inconspicuous with the push of a button - the customizable mode button in the device center will turn off all lights and sounds at it's default configuration, but can be reconfigured to launch any RouterOS script.

Summary: Mikrotik cAP ac. 2.4 GHz, 5 GHz, Maximum data transfer rate: 867 Mbit/s, Ethernet LAN data rates: 10,100,1000 Mbit/s. Power over Ethernet (PoE). Product colour: White. Power consumption (max): 13 W | Vendor Homepage: https://mikrotik.com/product/cap_ac#fndtn-specifications | 2.4 GHz: Yes | 5 GHz: Yes | Ethernet LAN data rates: 10/100/1000 | Frequency band: 2.412 - 2.484, 5.15 - 5.875 | Maximum data transfer rate: 867 | Maximum data transfer rate (2.4 GHz): 300 | Maximum data transfer rate (5 GHz): 867 | Networking standards: IEEE 802.11a/IEEE 802.11ac/IEEE 802.11b/IEEE 802.11g/IEEE 802.11n/IEEE 802.3af/IEEE 802.3at | Receiver sensitivity: 2.4GHz: 1MBit/s: -100 @ 26dBm Tx 11MBit/s: -94 @ 26dBm Tx 6MBit/s: -96 @ 26dBm Tx 54MBit/s: -78 @ 23dBm Tx MCS0: -96 @ 26dBm Tx MCS7: -73 @ 22dBm Tx 5GHz: 6MBit/s: -96 @ 26dBm Tx 54MBit/s: -80 @ 21dBm Tx MCS0: -96 @ 26dBm Tx MCS7: -75 @ 20dBm Tx MCS9: -7 | Ethernet LAN (RJ-45) ports: 2 | DC voltage range: 17 - 57 | Output voltage: 57 | Power consumption (max): 13 | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) type supported: Active PoE/Passive PoE | Internal: No | LED indicators: Yes | Placement: Ceiling,Wall | Product colour: White | Antenna features: Integrated antenna | Antenna gain level (max): 2.5 | Antenna type: Internal | Antennas quantity: 4 | Built-in processor: Yes | Flash memory: 16 | Internal memory: 128 | Operating system installed: RouterOS | Processor frequency: 716 | Processor model: IPQ4018 | Certification: CE, FCC, IC, EAC, ROHS | Depth: 30 | Height: 136 | Width: 136 | AC adapter included: Yes | Mounting kit: Yes | PoE adapter included: Yes | Operating temperature (T-T): -40 - 50 | Harmonized System (HS) code: 85176990 | Model name: cAP ac // RBcAPGi-5acD2nD | Units per Pallet: 0 | Units per Shipping Box: 20 | Unit Calculated Volume: 0.003386 | Unit Calculated Weight: 0.718

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950