

Switch TP-LINK

Switch type

Unmanaged

24xRJ-45 ports

RJ-45 Ports Type

Gigabit Ethernet

(10/100/1000)

LS1024G



Model: LS1024G

Manufacturer: TP-LINK

EAN: 1210002602136

Product Code: 194376

R1,528

The LS1024G Gigabit Ethernet Switch provides you with a high-performance, low-cost, easy-to-use, seamless and standard upgrade to improve old network to 1000Mbps network. All 24 ports support auto MDI/MDIX, no need to worry about the cable type, simply plug and play. Moreover, with the innovative energy-efficient technology, the LS1024G can save power consumption, making it an eco-friendly solution for your business network.

- Supports MAC address self-learning, Auto MDI/MDIX and Auto Negotiation

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

- Plug & play design
- QoS ensures smooth traffic for latency sensitive applications such as voice or video
- Innovative energy-efficient technology saves power consumption
- Fanless design reduces power consumption and ensures silent operation, ideal for noise-sensitive homes or businesses
- Durable metal casing provides improved heat dissipation and ensures a longer product life
- Desktop or rackmount installation

Summary: TP-Link LS1024G. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 24. MAC address table: 8000 entries, Switching capacity: 48 Gbit/s. Networking standards: IEEE 802.3, IEEE 802.3ab, IEEE 802.3i, IEEE 802.3p, IEEE 802.3u, IEEE 802.3x | Vendor Homepage: <https://www.tp-link.com/au/business-networking/soho-switch-unmanaged/ls1024g/> | Switch type: Unmanaged | Basic switching RJ-45 Ethernet ports quantity: 24 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | 10G support: No | Auto MDI/MDI-X: Yes | Auto-negotiation: Yes | Copper ethernet cabling technology: 1000BASE-T/100BASE-TX/10BASE-T | Networking standards: IEEE 802.3/IEEE 802.3ab/IEEE 802.3i/IEEE 802.3p/IEEE 802.3u/IEEE 802.3x | Forwarding rate: 35.712 | Jumbo frames: 10000 | Jumbo frames support: Yes | MAC address table: 8000 | Packet buffer memory: 2 | Store-and-forward: Yes | Switching capacity: 48 | Product colour: Black | Rack mounting: No | Fanless: Yes | Mean time between failures (MTBF): 1183684 | AC input frequency: 50/60 | AC input voltage: 100 - 240 | Input current: 0.6 | Power consumption (max): 12.6 | Power source: AC | Power supply included: Yes | Heat dissipation: 42.77 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): 0 - 45 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -40 - 70 | Depth: 140 | Height: 44 | Width: 294 | Cables included: Power | Rack mount kit: Yes | User guide: Yes | Compliance certificates: CE/Federal Communications Commission (FCC)/RoHS | Model: LS1024G | Units per Shipping Box: 1 | Unit Calculated Volume: 0.006392 | Unit Calculated Weight: 1.95

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950