

Switch TELTONIKA TSW100000000 PoE+ ports 4 120 Watts TSW100



Model: TSW100

Manufacturer: TELTONIKA

EAN: 4779027312828

Product Code: 194380

R1,682

TSW100 – 5-port, unmanaged full Gigabit Ethernet switch supporting Power-over-Ethernet (802.3af and 802.3at standards). This device is classified as power source equipment (PSE), and when used in this way, TSW100 switch enables centralization of the power supply, providing up to 30 watts of power per port and reducing the effort for installing power. It has 10/100/1000 Mbps Ethernet ports to provide an economical high-bandwidth solution for your industrial Ethernet network.

Summary: Teltonika TSW100. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 5. MAC address table: 2000 entries. Networking standards: IEEE 802.3af, IEEE 802.3at, IEEE 802.3az. DC input voltage: 7 - 58 V. Power over Ethernet (PoE) | Vendor Homepage: <https://teltonika-networks.com/product/tsw100/#features> | Basic switching RJ-45 Ethernet ports quantity: 5 | Basic switching RJ-45 Ethernet ports type: Gigabit

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Ethernet (10/100/1000) | Auto MDI/MDI-X: Yes | Networking standards: IEEE 802.3af/IEEE 802.3at/IEEE 802.3az | Jumbo frames: 9216 | MAC address table: 2000 | Packet buffer memory: 0.128 | Housing material: Aluminium | LED indicators: Power/Status | Product colour: Blue/Metallic | DC input voltage: 7 - 58 | Power consumption (max): 129 | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) ports quantity: 4 | Power over Ethernet (PoE) power per port: 30 | Total Power over Ethernet (PoE) budget: 120 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -40 - 75 | Depth: 95 | Height: 32 | Width: 115 | Certification: CE/RED, EAC, RoHS, WEEE Draft ETSI EN 301 489-1 V2.2.0, Draft EN 301 489-19 V2.1.0, Draft ETSI EN 301 489-52 V1.1.0 EN 61000-4-2:2009 EN 300 511 V12.5.1, ETSI EN 301 908-1 V11.1.1, ETSI EN 301 908-2 V11.1.2, ETSI EN 301 908-13 V11.1.2 EN 61000-4-3:2006 + | Harmonized System (HS) code: 85176990 | Model: TSW100 | Model name: TSW100000000 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.001726 | Unit Calculated Weight: 0.74

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950