

Switch DAHUA Type L2 Desktop/pedestal Rack 1x10Base- T 100Base-TX 1000Base-T PoE ports 8 96 Watts DH-PFS3009- 8ET1GT-96-V2



Model: DH-PFS3009-8ET1GT-96-V2

Manufacturer: DAHUA

EAN: 6923172523242

Product Code: 194384

R1,446

DH-PFS3009-8ET-96 is an 8-port fast ethernet switch, which supports 250 meters long distance PoE transmission. It provides 8*10/100Mbps PoE ports and 1*100 Mbps uplink port. The product is equipped with two transmission modes (Default/Extend), which are controlled by DIP switch.

- Layer two commercial switch

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

- > Supports PoE power management
- > Supports wall-mount installation
- > Supports anti-theft lock hole
- > MAC auto learning and aging, MAC address capacity is 2K
- > Supports IEEE802.3, IEEE802.3u and IEEE802.3X standards
- > RJ45 port supports 10/100 Mbps self-adaptation
- > Supports 250 meters long distance PoE transmission
- > Conforms to IEEE802.3af and IEEE802.3at power supply standard. Port 1 supports Hi-PoE 60W power supply

Summary: Dahua Technology PFS3009-8ET-96. Switch type: Unmanaged, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100), Basic switching RJ-45 Ethernet ports quantity: 8. MAC address table: 2000 entries, Switching capacity: 1.8 Gbit/s. Networking standards: IEEE 802.3af, IEEE 802.3at. DC input voltage: 48 - 57 V. Power over Ethernet (PoE) | Vendor Homepage: <https://www.dahuasecurity.com/products/productDetail/12971> | Switch layer: L2 | Switch type: Unmanaged | Basic switching RJ-45 Ethernet ports quantity: 8 | Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100) | 10G support: No | Auto MDI/MDI-X: Yes | Flow control support: Yes | MAC address auto-aging supported: Yes | MAC address auto-learning supported: Yes | Networking standards: IEEE 802.3af/IEEE 802.3at | Forwarding rate: 1.34 | MAC address table: 2000 | Packet buffer memory: 0.768 | Switching capacity: 1.8 | Product colour: Black | Rack mounting: No | Stackable: No | DC input voltage: 48 - 57 | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) ports quantity: 8 | Total Power over Ethernet (PoE) budget: 96 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -10 - 55 | Depth: 100 | Height: 30 | Weight: 480 | Width: 190 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.005184 | Unit Calculated Weight: 1.25

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950