

Switch

TELTONIKA

TSW101000000

PoE ports 4 60

Watts TSW101



Model: TSW101

Manufacturer: TELTONIKA

EAN: 4779051840113

Product Code: 194401

R1,587

AUTOMOTIVE POE+ SWITCH

Our first-ever switch for the automotive industry features five Gigabit Ethernet ports with PoE+ support to connect multiple devices to the network and power them up using the same interfaces. Enjoy reliable high bandwidth connectivity in a simple, economical, and easy-to-install solution.

Summary: Teltonika TSW101. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 5. MAC address table: 2000 entries, Switching capacity: 10 Gbit/s. Networking standards: IEEE 802.3, IEEE 802.3az, IEEE 802.3u. Power connector: Terminal block (2-pin). Power over Ethernet (PoE) | Vendor Homepage: <https://teltonika-networks.com/products/switches/tsw101> | Basic switching RJ-45 Ethernet ports quantity: 5 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Power connector: Terminal block (2-pin) | 10G support: No | Auto MDI/MDI-X: Yes | Ethernet LAN data rates: 10,100,1000 |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Networking standards: IEEE 802.3/IEEE 802.3az/IEEE 802.3u | Jumbo frames: 9216 | Jumbo frames support: Yes | MAC address table: 2000 | Switching capacity: 10 | Housing material: Aluminium | International Protection (IP) code: IP30 | LED indicators: Power/Status | Product colour: Metallic | Input voltage: 9 - 30 | Power consumption (max): 2.31 | Power consumption (typical): 0.64 | Power source: DC | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) ports quantity: 4 | Power over Ethernet (PoE) power per port: 30 | Power over Ethernet (PoE) type supported: Passive PoE | Total Power over Ethernet (PoE) budget: 120 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -40 - 75 | Depth: 32 | Height: 95 | Weight: 354 | Width: 115 | Certification: CE, REACH, RoHS, WEEE TSW101 CE TSW101 UKCA TSW101 FCC TSW101 IC TSW101 CB TSW101 RCM E-Mark | Harmonized System (HS) code: 851762 | Model: TSW101 | Model name: TSW101000000 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.0008925 | Unit Calculated Weight: 0.44

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950