

**Access Point**  
**MIKROTIK IEEE**  
**802.11 b/g IEEE**  
**802.11n IEEE**  
**802.11ac 5xRJ45**  
**USB 2.0**  
**RB952UI-**  
**5AC2ND-TC**



Model: RB952UI-5AC2ND-TC

Manufacturer: MIKROTIK

EAN: 4752224003225

Product Code: 194517

**R1,152**

The hAP ac lite is a Dual-concurrent Access Point, that provides Wifi coverage for 2.4GHz and 5GHz frequencies at the same time.

Unit is equipped with a 650MHz CPU, 64MB RAM, five 10/100Mbps Ethernet ports (PoE output on port #5), dual-chain 802.11b/g/n 2.4GHz wireless, single chain 802.11ac 5GHz wireless, USB port for 3G/4G modem and a RouterOS L4 license.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

New design universal case allows unit to be positioned either horizontally (desktop) or vertically (tower case). Wall anchored mounting kit is provided.

We have two versions available - RB952Ui-5ac2nD-TC (International) and RB952Ui-5ac2nD-TC-US (USA). RB952Ui-5ac2nD-TC-US (USA) is factory locked for 2412-2462MHz, 5170-5250MHz and 5725-5835MHz frequencies. This lock can not be removed. RB952Ui-5ac2nD-TC (International) supports 2412-2484MHz and 5150MHz - 5875MHz range.

Summary: Mikrotik hAP ac lite tower. 2.4 GHz, 5 GHz, Ethernet LAN data rates: 10,100 Mbit/s. Power over Ethernet (PoE). Product colour: Black. Power consumption (max): 7 W | Vendor Homepage: <https://mikrotik.com/product/RB952Ui-5ac2nD-TC> | 2.4 GHz: Yes | 5 GHz: Yes | Ethernet LAN data rates: 10/100 | Networking standards: IEEE 802.11a/IEEE 802.11ac/IEEE 802.11b/IEEE 802.11g/IEEE 802.11n | Ethernet LAN (RJ-45) ports: 5 | USB 2.0 ports quantity: 1 | USB connector type: USB Type-A | AC input voltage: 8 - 30 | Power consumption (max): 7 | Power over Ethernet (PoE): Yes | Internal: No | LED indicators: Yes | Placement: Table | Product colour: Black | Antenna gain level (max): 15 | Flash memory: 16 | Depth: 98 | Height: 34 | Width: 119 | Harmonized System (HS) code: 85176990 | Model name: hAP ac lite TC // RB952Ui-5ac2nD-TC | Units per Pallet: 0 | Units per Shipping Box: 20 | Unit Calculated Volume: 0.001519 | Unit Calculated Weight: 0.44

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950