

Switch TP-LINK Desktop/pedestal 5x10Base-T 100Base-TX 1000Base-T PoE ports 4 TL- SG105PE



Model: TL-SG105PE

Manufacturer: TP-LINK

EAN: 6935364052744

Product Code: 194582

R962

The TL-SG105PE is an 5-port Gigabit Easy Smart Switch with 4 PoE+ ports, represents a powerful upgrade from an unmanaged switch. It is designed specially for small businesses that require simple network management and PoE function. The TL-SG105PE can connect and power up to four PoE devices, such as wireless access points (APs), IP cameras, and IP phones. Through its web-based user interface and management utility, the TL-SG105PE offers a variety of useful features, including network monitoring, traffic prioritization, PoE Auto Recovery and enhanced QoS. Additionally, with port-based, tag-based and MTU VLAN, TL-SG105PE can improve security and meet more network segmentation requirements.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Power Over Ethernet

4 of the 5 Auto-Negotiation RJ45 ports (port 1 to port 4) of the switch support Power over Ethernet (PoE) function. These PoE ports can automatically detect and supply power with those IEEE 802.3af/at compliant Powered Devices (PDs).

Overload Arrangement

TL-SG105PE has the priority function which will help protect the system when the system power is overloaded. If all PoE PDs power consumption is ≥ 65 W, a priority will be arranged among the PoE ports, then the system will cut off the power of the lowest-priority port.

Intelligent Power Management

Priority (port 1 > port 2 > port 3 > port 4): This function will help protect the system if the system power becomes overloaded. For example, Port 1, 2 and 4 are consuming 15.4 W respectively. If an additional PoE device with 20 W is inserted to port 3, the system will cut off the power of port 4 to compensate for the overload.

Effective Management

TL-SG105PE offers network monitoring for users to observe traffic behavior. Through its web-based user interface and management utility, the TL-SG105PE offers a variety of useful features, including network monitoring, traffic prioritization, PoE Auto Recovery and enhanced QoS.

With Port Mirroring, Loop Prevention and Cable Diagnostics features, TL-SG105PE can identify and even locate connection problems on your business network. Also, administrators can designate the priority of the traffic based on Port Priority, 802.1P Priority and DSCP Priority, to ensure that voice and video are always clear, smooth and lag-free.

Additionally, to improve security and network performance, TL-SG105PE supports MTU VLAN, port-based VLAN and 802.1Q-based VLAN functions. PoE Auto Recovery automatically reboots your dropped or unresponsive PoE-powered devices.

TL-SG105PE is an upgrade from the plug-and-play Unmanaged Switch, delivering great value while empowering your network and similarly delivering great value to the end user.

Easy to Use

TL-SG105PE is easy to use and manage. Auto MDI/MDI-X crossover on all ports eliminate the need for crossover cables or uplink ports. Auto-negotiation on each port senses the link speed of a network

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

device (either 10, 100, or 1000 Mbps) and intelligently adjusts for compatibility and optimal performance. Its compact size makes it ideal for desktops with limited space. Dynamic LED lights provide real-time work status display and basic fault diagnosis.

- Five 10/100/1000Mbps RJ45 ports
- Equipped with four 802.3af/at PoE+ ports with up to 30W for each port, data and power can be transferred on one single cable
- Supports PoE power up to 65 W for all PoE ports
- Provides network monitoring, traffic prioritization, VLAN features, and PoE Auto Recovery
- Simple network set-up on top of plug-and-play connectivity
- Web-based user interface and Easy Smart Configuration Utility simplify configuration

Summary: TP-Link 5-Port Gigabit Easy Smart PoE Switch with 4-Port PoE+. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 5. MAC address table: 2000 entries, Switching capacity: 10 Gbit/s. Networking standards: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE.... Power over Ethernet (PoE) | Vendor Homepage: <https://www.tp-link.com/uk/business-networking/easy-smart-switch/tl-sg105pe/> | Quality of Service (QoS) support: Yes | Switch layer: L2 | Switch type: Managed | Web-based management: Yes | Basic switching RJ-45 Ethernet ports quantity: 5 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Gigabit Ethernet (copper) ports quantity: 5 | 10G support: No | Auto MDI/MDI-X: Yes | Auto-negotiation: Yes | Broadcast storm control: Yes | Cable types supported: Cat3/Cat4/Cat5/Cat5e/Cat6 | Copper ethernet cabling technology: 1000BASE-T/100BASE-FX/100BASE-TX/10BASE-T | Flow control support: Yes | Link aggregation: Yes | Networking standards: IEEE 802.1p/IEEE 802.1Q/IEEE 802.3ab/IEEE 802.3af/IEEE 802.3at/IEEE 802.3i/IEEE 802.3u/IEEE 802.3x | Number of VLANs: 4000 | Port mirroring: Yes | Rate limiting: Yes | Virtual LAN features: Port-based VLAN/Tagged VLAN | VLAN support: Yes | Forwarding rate: 7.44 | Jumbo frames: 16000 | Jumbo frames support: Yes | MAC address table: 2000 | Number of queues: 4 | Packet buffer memory: 1 | Store-and-forward: Yes | Switching capacity: 10 | IGMP snooping: Yes | Loop protection: Yes | LED indicators: Activity/Link/PoE/Power/Speed/Status | Product colour: Black | Rack mounting: No | Fanless: Yes | Input current: 1.31 | Input voltage: 53.5 | Power consumption (max): 75.16 | Power source: DC | Power supply included: Yes | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) power per port: 30 | Power over Ethernet plus (PoE+) ports quantity: 4 | Total Power over Ethernet (PoE) budget: 65 | Heat dissipation: 256.3 | Operating relative humidity (H-H): 10 - 90 |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Operating temperature (T-T): 0 - 40 | Storage relative humidity (H-H): 5 - 95 | Storage temperature (T-T): -40 - 70 | Depth: 98 | Height: 25 | Width: 99.8 | User guide: Yes | Package depth: 196 | Package height: 121 | Package weight: 770 | Package width: 131 | Certification: FCC, CE, RoHS | Harmonized System (HS) code: 85176990 | Model: TL-SG105PE | Units per Pallet: 0 | Units per Shipping Box: 12 | Unit Calculated Volume: 0.003822 | Unit Calculated Weight: 0.875

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950