

Switch TP-LINK Desktop/pedestal 9x10Base-T 100Base-TX PoE+ ports 8 TL- SF1009P



Model: TL-SF1009P

Manufacturer: TP-LINK

EAN: 6935364052966

Product Code: 194601

R912

Professional 9-Port Unmanaged Switch with 8 PoE+ Ports

Plug and Play, with PoE Transmission for Surveillance up to 250 m

Professional 9-Port Switch with 8-Port PoE+ (65 W Budget) for Numerous Applications

Compliance with the 802.3af/at PoE+ standard supports up to 30 W on each PoE port. The total 65 W PoE power budget* for the 8× PoE+ ports opens up a wide range of applications, such as surveillance for offices, dormitories, and small businesses. It is fully compatible with IP cameras, access points, IP phones, computers, printers, and more.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Ideal for IP Surveillance

—Up to 250 m Transmissions

With extend mode, the PoE transmission distance reaches up to 250 m**—perfect for IP Camera deployment in large areas.

**The speed of the ports in extend mode will downgrade to 10 Mbps. The actual transmission distance may vary due to power consumption of PoE-powered devices or the cable quality and type.

Ideal for IP Surveillance

—Higher Performance and Security

Priority Mode and Isolation Mode make surveillance smoother and safer.

Intelligent Power Management

When total power consumption exceeds 65 W, the intelligent power management will cut the lower priority port power. This ensures the high priority port's power supply and protects the device from power overload. It also automatically detects and provides the required power for your PoE devices while protecting your PoE and non-PoE equipment from being damaged.

Durable Metal Casing

The interior components of TL-SF1009P are protected by high-quality metal casing to ensure a long product life. Having passed an array of stringent reliability tests, TL-SF1009P delivers switching performance you can depend on.

- 9× 10/100 Mbps RJ45 ports
- 8× PoE+ ports transfer data and power on individual cables
- Works with IEEE 802.3af/at compliant PDs
- Supports PoE Power up to 30 W for each PoE port
- Supports PoE Power up to 65 W for 8 PoE ports*
- Up to 250 m data and power transmitting range under Extend Mode**
- Priority Mode ensures high priority of ports 1–2 to guarantee the quality of sensitive application
- Isolation Mode allows one-click client traffic separation for higher security and performance
- Plug and play with no configuration required

Summary: TP-Link 9-Port 10/100Mbps Desktop Switch with 8-Port PoE+. Switch type: Unmanaged.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100), Basic switching RJ-45 Ethernet ports quantity: 9. Full duplex. MAC address table: 2000 entries, Switching capacity: 1.6 Gbit/s. Networking standards: IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x. DC input voltage: 53.5 V. Power connector: DC-in jack. Power over Ethernet (PoE). Wall mountable | Vendor Homepage: <https://www.tp-link.com/uk/business-networking/unmanaged-switch/tl-sf1009p/> | Switch type: Unmanaged | Basic switching RJ-45 Ethernet ports quantity: 9 | Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100) | Fast Ethernet (copper) ports quantity: 9 | Power connector: DC-in jack | 10G support: No | Auto MDI/MDI-X: Yes | Auto-negotiation: Yes | Cable types supported: Cat3/Cat4/Cat5/Cat5e | Copper ethernet cabling technology: 100BASE-TX/10BASE-T | Flow control support: Yes | Full duplex: Yes | Half duplex: Yes | MAC address auto-aging supported: Yes | MAC address auto-learning supported: Yes | Networking standards: IEEE 802.3af/IEEE 802.3at/IEEE 802.3i/IEEE 802.3u/IEEE 802.3x | Forwarding rate: 1.3392 | MAC address table: 2000 | Store-and-forward: Yes | Switching capacity: 1.6 | Housing material: Metal | LED indicators: Activity/Link/PoE/Power | Product colour: Black | Rack mounting: No | Stackable: No | Wall mountable: Yes | Fanless: Yes | AC input frequency: 50 | AC input voltage: 220 | DC input voltage: 53.5 | Input current: 1.31 | Power consumption (max): 77.08 | Power source: DC/PoE | Power supply included: No | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) power per port: 30 | Power over Ethernet plus (PoE+) ports quantity: 8 | Total Power over Ethernet (PoE) budget: 65 | Heat dissipation: 262.84 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): 0 - 40 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -40 - 70 | Depth: 98 | Height: 27 | Width: 171 | User guide: Yes | AC adapter included: Yes | Package depth: 280 | Package height: 68 | Package type: Box | Package weight: 980 | Package width: 223 | Sustainability compliance: Yes | Certification: FCC, CE, RoHS | Compliance certificates: CE/Federal Communications Commission (FCC)/RoHS | Harmonized System (HS) code: 85176990 | Model: TL-SF1009P | Model name: 9-Port 10/100Mbps Desktop Switch with 8-Port PoE+ | Units per Pallet: 0 | Units per Shipping Box: 12 | Unit Calculated Volume: 0.005225 | Unit Calculated Weight: 1.1

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950