

Switch TP-LINK LS108GP PoE+ ports 8 LS108GP



Model: LS108GP

Manufacturer: TP-LINK

EAN: 4895252505986

Product Code: 194606

R895

The TP-Link LiteWave Series PoE Switches require no configuration and provide PoE (Power over Ethernet) ports. They can automatically detect and supply power with all IEEE 802.3af/at compliant Powered Devices (PDs). In this situation, the electrical power is transmitted along with data in one single cable allowing you to expand your network to where there are no power lines or outlets, where you wish to fix devices such as APs, IP Cameras or IP Phones, etc.

- Full Gigabit Ports: Eight gigabit auto-negotiation ports provide up to 16 Gbps switching capacity
- 62 W PoE Budget: Eight gigabit 802.3af/at-compliant PoE+ ports easily connect and power fixed devices like IP cameras, access points, and IP phones via a single cable. Up to 30 W PoE output is supported by each PoE port
- Up to 250 m PoE Transmission: With Extend Mode, PoE transmission distance reaches up to 250m, perfect for surveillance camera deployment in large areas
- PoE Auto Recovery: Automatically reboots your dropped or unresponsive PoE-powered devices

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

- Plug and Play: Simply plug and play for instant connectivity with no configuration required
- Silent Operation: Fanless design reduces power consumption and ensures silent operation, ideal for noise-sensitive homes or businesses
- Reliable Hardware Design: Durable metal casing and desktop/wall-mounting design are well-suited for different environments

Summary: TP-Link LiteWave 8-Port Gigabit Desktop Switch with 8-Port PoE+. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 8. MAC address table: 4000 entries, Switching capacity: 16 Gbit/s. Networking standards: IEEE 802.1p, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE.... DC input voltage: 53.5 V. Power connector: DC-in jack. Power over Ethernet (PoE) | Vendor Homepage: <https://www.tp-link.com/uk/business-networking/soho-switch-poe/ls108gp/> | Quality of Service (QoS) support: Yes | Switch type: Unmanaged | Basic switching RJ-45 Ethernet ports quantity: 8 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Power connector: DC-in jack | 10G support: No | Auto MDI/MDI-X: Yes | Auto-negotiation: Yes | Cable types supported: Cat3/Cat4/Cat5/Cat5e | Flow control support: Yes | Networking standards: IEEE 802.1p/IEEE 802.3ab/IEEE 802.3af/IEEE 802.3at/IEEE 802.3i/IEEE 802.3u/IEEE 802.3x/IEEE 802.3z | Forwarding rate: 11.9 | Jumbo frames: 16000 | MAC address table: 4000 | Switching capacity: 16 | LED indicators: Yes | Product colour: Black | AC input frequency: 50 | AC input voltage: 220 | DC input voltage: 53.5 | Input current: 1.31 | Power consumption (max): 71.61 | Power source: DC/PoE | Power supply included: Yes | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) power per port: 30 | Power over Ethernet plus (PoE+) ports quantity: 8 | Total Power over Ethernet (PoE) budget: 62 | Heat dissipation: 243.47 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): 0 - 40 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -40 - 70 | Depth: 99 | Height: 25 | Width: 158 | User guide: Yes | Package type: Box | Certification: CE, FCC, RoHS | Model name: LS108GP | Units per Pallet: 0 | Units per Shipping Box: 12 | Unit Calculated Volume: 0.003683 | Unit Calculated Weight: 0.85

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950