

## Switch DAHUA Desktop/pedestal 8x10Base-T 100Base-TX PoE ports 4 60 Watts SF1008LP



Model: SF1008LP

Manufacturer: DAHUA

EAN: 6923172572035

Product Code: 194615

## R876

DH-SF1008LP is an unmanaged Desktop Switch with 4 × 10/100 Mbps PoE Ports. It provides 8 × 10/100 Mbps Ethernet ports. The product is equipped with two types of transmission modes (Extend Mode On/

Extend Mode Off). The Orange port supports the Hi-PoE standards. It also supports PoE watchdog to avoid manually maintenance and device restart, which can realize the intelligent management and reduce the cost.

### Intelligent PoE

Provides control over power consumption and offers real-time monitoring to ensure power supplies

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

receive priority with important ports and to prevent malfunctions caused by changes in power consumption. Supports ultra wide power supplies and is able to adapt to IPC power fluctuations.

### **Hi-PoE 60W (Orange Port)**

In addition to the IEEE802.3af and IEEE802.3at standards, orange port also supports a maximum power output of 60W for powering high- power devices.

### **PoE Watchdog**

Adopts the innovative PoE Watchdog. PoE Watchdog can be switched on by dialing or turning on the WEB page switch. It enables the switch to automatically detect port status and restart failed ports to recover

connection in case of IPC connection exception. This enables intelligent operation and maintenance management in its truest sense, effectively reducing manual maintenance costs.

### **Long Distance PoE**

By dialing or enabling long-range transmission on the WEB interface, the transmission distance of a PoE port can be up to 250 m, meeting the requirements of wired transmission (bandwidth reduced to 10 Mbps).

### **8-pin Assignment PoE Power Supply**

Supports 8-pin simultaneous power supply (1/2/4/5 positive, 3/6/7/8 negative). Signal lines and idle lines supply power at the same time. Compatibility with IPC is enhanced. Cable loss is reduced. Loading capacity is increased.

- Intelligent PoE
- Hi-PoE 60W (orange port)
- 8-pin assignment PoE power supply
- Long distance PoE
- PoE watchdog
- Wide working temperature

Summary: Dahua Technology PoE SF1008LP. Switch type: Unmanaged, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100), Basic switching RJ-45 Ethernet ports quantity: 8. Full duplex. MAC address table: 2048 entries, Switching capacity: 1.8 Gbit/s. Networking

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

standards: IEEE 802.3, IEEE 802.3u, IEEE 802.3x. DC input voltage: 48 - 57 V. Power over Ethernet (PoE). Wall mountable | Vendor Homepage: <https://www.dahuasecurity.com/products/All-Products/Transmission/IT-Channel-Products/PoE-Switch/SF1008LP> | Switch layer: L2 | Switch type: Unmanaged | Basic switching RJ-45 Ethernet ports quantity: 8 | Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100) | Fast Ethernet (copper) ports quantity: 8 | 10G support: No | Auto MDI/MDI-X: Yes | Copper ethernet cabling technology: 100BASE-TX/10BASE-T | Ethernet LAN data rates: 10,100 | Flow control support: Yes | Full duplex: Yes | Networking standards: IEEE 802.3/IEEE 802.3u/IEEE 802.3x | Forwarding rate: 1.19 | MAC address table: 2048 | Packet buffer memory: 0.768 | Switching capacity: 1.8 | Housing material: Metal | LED indicators: Yes | Product colour: Black | Rack mounting: No | Wall mountable: Yes | DC input voltage: 48 - 57 | Power consumption (max): 60 | Power source: DC/PoE | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) ports quantity: 4 | Operating relative humidity (H-H): 5 - 95 | Operating temperature (T-T): -10 - 55 | Storage relative humidity (H-H): 5 - 95 | Storage temperature (T-T): -20 - 70 | Depth: 100 | Height: 30 | Weight: 490 | Width: 190 | Sustainability compliance: Yes | Compliance certificates: CE | Units per Pallet: 0 | Units per Shipping Box: 8 | Unit Calculated Volume: 0.005809 | Unit Calculated Weight: 1.19

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950