

Switch TP-LINK TL-SF1006P Desktop/pedestal 6x10Base-T 100Base-TX PoE+ ports 4 TL- SF1006P



Model: TL-SF1006P

Manufacturer: TP-LINK

EAN: 6935364030933

Product Code: 194650

R796

Professional High-Power Switch with 4 PoE+ Ports

Plug and Play, with PoE Transmission for Surveillance up to 250 m

Dedicated 4-Port PoE+ Switch (67 W Budget) for Numerous Applications

Compliance with the 802.3af/at PoE standard supports up to 15.4 W on each PoE port. The total 41 W PoE power budget* for the 4x PoE ports opens up a wide range of applications, such as surveillance for offices, dormitories, and small businesses. It is fully compatible with IP cameras, access points, IP phones, computers, printers, and more.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Ideal for IP Surveillance—Up to 250 m Transmissions

With extend mode, the PoE transmission distance reaches up to 250 m**—perfect for IP Camera deployment in large areas.

**The speed of the ports in extend mode will downgrade to 10 Mbps. The actual transmission distance may vary due to power consumption of PoE-powered devices or the cable quality and type.

Priority Video Quality Guaranteed

Quality of sensitive applications like video monitoring in critical business areas is guaranteed by offering higher priority options for ports 1–2 when one-touch Priority Mode is on.

Intelligent Power Management

When total power consumption exceeds 67 W, the intelligent power management will cut the lower priority port power. This ensures the high priority port's power supply and protects the device from power overload. It also automatically detects and provides the required power for your PoE devices while protecting your PoE and non-PoE equipment from being damaged.

Durable Metal Casing

The interior components of TL-SF1006P are protected by high-quality metal casing to ensure a long product life. Having passed an array of stringent reliability tests, TL-SF1006P delivers switching performance you can depend on.

- 6× 10/100 Mbps RJ45 ports
- 4× PoE+ ports transfer data and power on individual cables
- Works with IEEE 802.3af/at compliant PDs
- Up to 250m data and power transmitting range under Extend Mode**
- Priority Mode ensures high priority of ports 1–2 to guarantee the quality of sensitive application
- Supports PoE Power up to 30 W for each PoE port
- Supports PoE Power up to 67 W for all PoE ports*
- Plug and play with no configuration required

Summary: TP-Link TL-SF1006P. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100), Basic switching RJ-45 Ethernet ports quantity: 6. Full duplex. MAC address table: 2000 entries, Switching capacity: 1.2 Gbit/s. Networking standards: IEEE 802.3af, IEEE 802.3at. DC input voltage: 53.5 V. Power over Ethernet (PoE) | Vendor Homepage: <https://www.tp->

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

link.com/uk/business-networking/poe-switch/tl-sf1006p/#overview | Switch type: Unmanaged | Basic switching RJ-45 Ethernet ports quantity: 6 | Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100) | 10G support: No | Auto MDI/MDI-X: Yes | Auto-negotiation: Yes | Cable types supported: Cat3/Cat4/Cat5/Cat5e | Copper ethernet cabling technology: 100BASE-T/100BASE-TX/10BASE-T | Flow control support: Yes | Full duplex: Yes | Half duplex: Yes | MAC address auto-aging supported: Yes | MAC address auto-learning supported: Yes | Networking standards: IEEE 802.3af/IEEE 802.3at | Forwarding rate: 0.8928 | Jumbo frames: 2000 | Jumbo frames support: Yes | MAC address table: 2000 | Store-and-forward: Yes | Switching capacity: 1.2 | Housing material: Metal | LED indicators: Yes | Product colour: Black | Rack mounting: No | Stackable: No | Fanless: Yes | AC input frequency: 50 | AC input voltage: 220 | DC input voltage: 53.5 | Input current: 1.31 | Power consumption (max): 74 | Power source: DC/PoE | Power supply included: Yes | Power over Ethernet (PoE): Yes | Power over Ethernet plus (PoE+) ports quantity: 4 | Total Power over Ethernet (PoE) budget: 67 | Heat dissipation: 252.34 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): 0 - 40 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -40 - 70 | Depth: 101 | Height: 25 | Width: 158 | User guide: Yes | AC adapter included: Yes | Package depth: 196 | Package height: 121 | Package type: Box | Package weight: 870 | Package width: 131 | Sustainability compliance: Yes | Certification: FCC, CE, RoHS | Compliance certificates: CE/Federal Communications Commission (FCC)/RoHS | Harmonized System (HS) code: 85176990 | Model name: TL-SF1006P | Units per Shipping Box: 12 | Unit Calculated Volume: 0.003959 | Unit Calculated Weight: 0.933

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950