

**Wireless Router
TP-LINK Wi-Fi 5
(802.11ac) Data
speed 1200
Mbit/s Ethernet
WAN Yes
Ethernet LAN
Yes 4xLAN ports
ARCHERC64**



Model: ARCHERC64

Manufacturer: TP-LINK

EAN: 4897098683217

Product Code: 194652

R733

WRL ROUTER 1200MBPS 1000M 4P/DUAL BAND ARCHER C64 TP-LINK

Summary: TP-Link Archer C64. Wi-Fi band: Dual-band (2.4 GHz / 5 GHz), Top Wi-Fi standard: Wi-Fi 5 (802.11ac), WLAN data transfer rate (max): 1200 Mbit/s. Ethernet LAN interface type: Gigabit Ethernet, Networking standards: IEEE 802.1x, Receiver sensitivity: 5 GHz: 11a 6Mbps:-95dBm 11a 54Mbps:-77dBm 11ac VHT20 MCS8:-71dBm 11ac VHT40 MCS9:-67dBm 11ac VHT80.... Security

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

algorithms: WPA, WPA-Enterprise, WPA2, WPA2-Enterprise, WPA3, Firewall security: SPI. Supported network protocols: IPv4, IPv6. Product type: Tabletop router, Product colour: Black | Vendor Homepage: <https://www.tp-link.com/> | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Wi-Fi standards: 802.11a/802.11b/802.11g/Wi-Fi 4 (802.11n)/Wi-Fi 5 (802.11ac) | WLAN data transfer rate (first band): 400 | WLAN data transfer rate (max): 1200 | WLAN data transfer rate (second band): 867 | 3G/4G USB modem compatibility: No | Ethernet WAN: Yes | SIM card slot: No | Dynamic DNS (DDNS): Yes | Ethernet LAN: Yes | Ethernet LAN interface type: Gigabit Ethernet | Networking standards: IEEE 802.1x | Port forwarding: Yes | Port triggering: Yes | Receiver sensitivity: 5 GHz: 11a 6Mbps:-95dBm 11a 54Mbps:-77dBm 11ac VHT20 MCS8:-71dBm 11ac VHT40 MCS9:-67dBm 11ac VHT80 MCS9:-63dBm 2.4 GHz: 11g 6Mbps: -96dBm 11g 54Mbps: -78dBm 11n HT20 MCS7:-77dBm 11n HT40 MCS7:-74dBm 11ac VHT20 MCS8:-73dBm 11ac VHT40 MCS9:-68dBm | Ethernet LAN (RJ-45) ports: 4 | USB port: No | MU-MIMO technology: Yes | Quality of Service (QoS) support: Yes | Reset button: Yes | Web-based management: Yes | WPS push button: Yes | DMZ support: Yes | Filtering: Yes | Firewall: Yes | Firewall security: SPI | Guest access: Yes | Parental control: Yes | Security algorithms: WPA/WPA2/WPA2-Enterprise/WPA3/WPA-Enterprise | URL filtering: Yes | DHCP client: Yes | DHCP server: Yes | Supported network protocols: IPv4, IPv6 | Universal Plug and Play (UPnP): Yes | Product colour: Black | Product type: Tabletop router | AC adapter included: Yes | Cables included: LAN (RJ-45) | Certification: CE, RoHS | Quick installation guide: Yes | Antenna design: External | Antennas quantity: 4 | Transmit power: CE: 20dBm(2.4 GHz), 23dBm(5.15 GHz~5.25 GHz) FCC: 30dBm(2.4 GHz & 5 GHz) | Built-in processor: Yes | Firmware upgradeable: Yes | Processor frequency: 1200 | Output current: 1 | Output voltage: 12 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): 0 - 40 | Storage relative humidity (H-H): 5 - 90 | Linux operating systems supported: Yes | Mac compatibility: Yes | Mac operating systems supported: Yes | Windows operating systems supported: Windows 10/Windows 2000/Windows 7/Windows 8/Windows 8.1/Windows 98SE/Windows NT/Windows Vista/Windows XP | Depth: 120 | Height: 27.9 | Width: 120 | Harmonized System (HS) code: 85176990 | Units per Pallet: 0 | Units per Shipping Box: 10 | Unit Calculated Volume: 0.006232 | Unit Calculated Weight: 0.73

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950