

Switch TP-LINK LS109P PoE+ ports 8 LS109P



Model: LS109P

Manufacturer: TP-LINK

EAN: 4895252504620

Product Code: 194729

R663

Switch de sobremesa de 9 puertos a 10/100 Mbps con 8 puertos PoE+

- 63 W de potencia PoE. 8 puertos PoE+ Gigabit compatibles con 802.3af/at alimentan fácilmente dispositivos como cámaras IP, puntos de acceso y teléfonos IP a través de un único cable. Cada puerto PoE admite hasta 30 W de salida.
- Hasta 250 m de transmisión PoE. Con el modo de extensión, la distancia de transmisión PoE alcanza hasta 250 m, ideal para el despliegue de cámaras de vigilancia en grandes áreas.
- Recuperación automática PoE. Reinicia automáticamente los dispositivos alimentados por PoE que no respondan.
- Separación de tráfico. El modo de aislamiento permite separar el tráfico de clientes con un solo clic para evitar el snooping y tampering, además de aislar el broadcast storm.
- Plug and Play. Conectividad instantánea sin necesidad de configuración.
- Funcionamiento silencioso. El diseño sin ventilador reduce el consumo de energía y garantiza un funcionamiento silencioso, ideal para hogares o empresas.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

- Hardware fiable. Carcasa metálica duradera y diseño para montaje en sobremesa o pared adaptado a distintos entornos.

Alimentación a Través de Ethernet, Despliegue a Medida

Cumple con el estándar 802.3af/at PoE+, 61 W disponibles para todos los puertos PoE+, 30 W máx. por puerto.

Transmisiones de Hasta 250 m

Seguridad y Estabilidad en tu Red

Modo Aislamiento

Divide fácilmente el tráfico para evitar el snooping/tampering y broadcast storm.

Recuperación Automática PoE

Detecta y reinicia automáticamente los dispositivos que no responden.

- 63 W de Potencia PoE
- PoE+ de Largo Alcance (250 m)
- Gestión Inteligente de Energía
- Recuperación Automática PoE
- Montaje de Sobremesa o en Pared
- Plug and Play
- Funcionamiento Silencioso
- Carcasa de Metal

Summary: TP-Link LiteWave LS109P. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100), Basic switching RJ-45 Ethernet ports quantity: 9. MAC address table: 2000 entries, Switching capacity: 1.8 Gbit/s. Networking standards: IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x. DC input voltage: 53.5 V. Power over Ethernet (PoE). Wall mountable | Vendor Homepage: <https://www.tp-link.com/es/business-networking/soho-switch-poe/ls109p/#highlights> | Quality of Service (QoS) support: Yes | Switch type: Unmanaged | Basic switching RJ-45 Ethernet ports quantity: 9 | Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100) | 10G support: No | Auto MDI/MDI-X: Yes | Auto-negotiation: Yes | Cable types supported:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Cat3/Cat4/Cat5/Cat5e | Copper ethernet cabling technology: 100BASE-TX/10BASE-T | Flow control support: Yes | Networking standards: IEEE 802.3af/IEEE 802.3at/IEEE 802.3i/IEEE 802.3u/IEEE 802.3x | Forwarding rate: 1.3392 | Jumbo frames support: Yes | MAC address table: 2000 | Store-and-forward: Yes | Switching capacity: 1.8 | LED indicators: Yes | Number of fans: 0 | Product colour: Black | Wall mountable: Yes | Fanless: Yes | AC input frequency: 50 | AC input voltage: 220 | DC input voltage: 53.5 | Input current: 1.31 | Power consumption (max): 73.24 | Power source: DC/PoE | Power supply included: Yes | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) power per port: 30 | Power over Ethernet plus (PoE+) ports quantity: 8 | Heat dissipation: 249 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): 0 - 40 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -40 - 70 | Depth: 98 | Height: 27 | Width: 171 | User guide: Yes | Package type: Box | Certification: CE, FCC, RoHS | Model: TP-LINK LS109P | Model name: LS109P | Units per Pallet: 0 | Units per Shipping Box: 12 | Unit Calculated Volume: 0.00518 | Unit Calculated Weight: 0.9

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950