

Switch DAHUA 16xRJ-45 ports SF1016L



Model: SF1016L

Manufacturer: DAHUA

EAN: 6923172568601

Product Code: 194762

R616

The Device is a layer-2 commercial switch. It has a high-performance switching engine and a large buffer memory to ensure smooth video stream transmission. With a plastic and fanless design, the device provides a more cost-effective option for customers. The Device is an unmanaged switch, so it does not need to be configured through web interface, which simplifies installation.

- 16 × RJ-45 10/100 Mbps ports
- Wide operating temperature ranging from -10 °C to +55 °C
- Easy to install, and is plug and play
- Supports wall mount and desktop mount

Summary: Dahua Technology SF1016L. Switch type: Unmanaged, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100), Basic switching RJ-45 Ethernet ports quantity: 16. MAC address table: 8 entries, Switching capacity: 3.2 Gbit/s. Networking standards: IEEE 802.3u, IEEE 802.3x, IEEE 802.3. DC input voltage: 12 V. Form factor: Desktop/Wall-Mounting | Vendor Homepage: <https://transmission.dahuasecurity.com/en/product->

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

list/Home/SOHOSwitches/PlasticSwitch/SF1016L | Switch layer: L2 | Switch type: Unmanaged | Basic switching RJ-45 Ethernet ports quantity: 16 | Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100) | 10G support: No | Ethernet LAN data rates: 10,100 | Networking standards: IEEE 802.3/IEEE 802.3u/IEEE 802.3x | Forwarding rate: 2.38 | Jumbo frames: 1520 | Jumbo frames support: Yes | MAC address table: 8 | Switching capacity: 3.2 | Form factor: Desktop/Wall-Mounting | Product colour: Grey | DC input voltage: 12 | Input current: 0.5 | Power consumption (typical): 1.5 | Power source: DC | Storage relative humidity (H-H): 10 - 90 | Storage temperature (T-T): -40 - 60 | Depth: 120 | Height: 42 | Weight: 300 | Width: 160 | Package depth: 180 | Package height: 92 | Package weight: 600 | Package width: 207 | Model: SF1016L | Units per Pallet: 0 | Units per Shipping Box: 12 | Unit Calculated Volume: 0.004615 | Unit Calculated Weight: 0.675

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950